



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation  
Intel VC820(933 MHz Pentium III processor)

SPECint2000 = 410  
SPECint\_base2000 = 407

SPEC license #: 13 Tested by: Intel Corporation Test date: Jun-2000 Hardware Avail: May-2000 Software Avail: Oct-2000

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	299	468	296	473
175.vpr	1400	441	318	441	318
176.gcc	1100	300	366	300	366
181.mcf	1800	658	274	657	274
186.crafty	1000	204	490	204	490
197.parser	1800	548	328	548	328
252.eon	1300	286	454	286	454
253.perlbmk	1800	324	555	324	555
254.gap	1100	272	405	272	405
255.vortex	1900	283	670	280	679
256.bzip2	1500	419	358	405	370
300.twolf	3000	842	356	834	360

### Hardware

CPU: Pentium III processor (933 MHz, 133 MHz bus)  
CPU MHz: 933  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 16KBI + 16KBD on-die  
Secondary Cache: 256KB(I+D) on-die ECC  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 256 MB PC800 RDRAM  
Disk Subsystem: IBM DTLA 307030 ATA-66+  
Other Hardware: Creative Labs Annihilator Pro GeForce 256 DDR

### Software

Operating System: Windows 2000(Build 2195)  
Compiler: Intel C++ and Fortran Compiler 5.0, for Windows NT 4.0/Windows 2000, Microsoft Visual C++ 6.0 (for libraries), SmartHeap library V5.0  
File System: FAT32  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning: -QxK -Qipo_wp shlw32M.lib +FDO
shlw32M.lib is the SmartHeap library V5.0 from MicroQuill www.microquill.com
Portability flags:
175.vpr: -Op          176.gcc: -Dalloca=_alloca /F10000000 -Op
186.crafy: -DNT_i386
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip, 175.vpr, 176.gcc, 181.mcf, 186.crafty, 197.parser, 252.eon, 253.perlbmk, 254.gap:
-QxK -Qipo_wp +FDO shlw32M.lib
255.vortex, 256.bzip2, 300.twolf:
-QxK -Qipo_wp +FDO -Oa shlw32M.lib
Tested systems can be used with Shin-G ATX case, Sparkle Inc. power supply
Product description as of 06/2000:
http://developer.intel.com/design/motherbd/vc/
Motherboard available through Intel OEM Distribution channel. See
http://channel.intel.com/ for more information
The system bus runs at 133 MHz
```