



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Origin 3800 64X 400MHz R12k

SPECint_rate2000 = 259
SPECint_rate_base2000 = 241

SPEC license #: 4 | Tested by: SGI | Test date: Jul-2000 | Hardware Avail: Sep-2000 | Software Avail: Sep-2000

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	64	615	169	64	591	176
175.vpr	64	356	292	64	344	302
176.gcc	64	347	236	64	348	235
181.mcf	64	297	450	64	279	478
186.crafty	64	300	247	64	303	245
197.parser	64	639	209	64	602	222
252.eon	64	363	266	64	367	263
253.perlbnk	64	733	182	64	735	182
254.gap	64	512	159	64	508	161
255.vortex	64	639	221	64	352	401
256.bzip2	64	448	249	64	406	275
300.twolf	64	669	333	64	671	332

Hardware

CPU: R12000
 CPU MHz: 400
 FPU: Integrated
 CPU(s) enabled: 64 cores, 64 chips, 1 core/chip
 CPU(s) orderable: 16-512
 Parallel: No
 Primary Cache: 32KBI + 32KBD on chip
 Secondary Cache: 8MB(I+D) off chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 64GB
 Disk Subsystem: 1 x 18 GB FC, 15 x 18 GB FC (striped)
 Other Hardware: None

Software

Operating System: IRIX 6.5.9m
 Compiler: MIPSpro 7.3.1.1m C, C++, Fortran90
 SCSSL 1.2 Math Library
 File System: xfs
 System State: Single-user

Notes/Tuning Information

Baseline optimization flags (C and C++ use same flags):

PASS1 : -Ofast=ip27 -IPA:use_intrinsic -fb_create /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)
 PASS2 : -Ofast=ip27 -IPA:use_intrinsic -fb_opt /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)

Portability Flags:

176.gcc: -DUSG -Dalloca=__builtin_alloca -DMIPS -DHOST_WORDS_BIG_ENDIAN
 186.crafty: -DSGI
 253.perlbnk: -DSPEC_CPU2000_SGI -DI_FCNTL
 254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_IOCTL_PROTO
 300.twolf: -DHAVE_SIGNED_CHAR

Peak optimization flags:

note: all occurrences of (FEEDBACK) below means compiled with a two-step process:

PASS1 = -fb_create /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
 PASS2 = -fb_opt /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
 164.gzip: -Ofast=ip27 -IPA:space=500:plimit=500 -lmalloc (FEEDBACK)
 175.vpr: -Ofast=ip27 -IPA:space=300:plimit=10000:callee_limit=5000:linear=on -LNO:prefetch Ahead=2
 . -INLINE:aggressive=on -OPT:Olimit=0:alias=disjoint:alias=restrict -lmalloc (FEEDBACK)
 181.mcf: -Ofast=ip27 -IPA:min_hot=14 -lmalloc (FEEDBACK)
 176.gcc: -Ofast=ip27 (FEEDBACK)
 186.crafty: -Ofast=ip27 -LNO:prefetch=0 -OPT:goto=off -lmalloc (FEEDBACK)
 197.parser: -Ofast=ip27 -IPA:min_hot=14 (FEEDBACK)



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI

SGI Origin 3800 64X 400MHz R12k

SPECint_rate2000 = 259

SPECint_rate_base2000 = 241

SPEC license #: 4 | Tested by: SGI | Test date: Jul-2000 | Hardware Avail: Sep-2000 | Software Avail: Sep-2000

Notes/Tuning Information (Continued)

```

252.eon: -Ofast=ip27 -LNO:prefetch=0 -LANG:exceptions=off -lmalloc (FEEDBACK)
253.perlbnk: -Ofast=ip27 -IPA:use_intrinsic -Wl,-x (FEEDBACK)
254.gap: -Ofast=ip27 -IPA:use_intrinsic -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4
. -OPT:alias=restrict:alias=disjoint -IPA:min_hot=7 -lmalloc (FEEDBACK)
255.vortex: -Ofast=ip27 -IPA:use_intrinsic -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4 -LNO:opt=0
. -CG:ld_latency=5 -IPA:min_hot=14 -TENV:X=4 -IPA:space=500:plimit=3600 -OPT:goto=off (FEEDBACK)
256.bzip2: -Ofast=ip27 -IPA:min_hot=5:space=500:plimit=2900 -INLINE:aggressive=on (FEEDBACK)
300.twolf: -Ofast=ip27 -IPA:use_intrinsic (FEEDBACK)

```

The following O/S parameters were set:

```

setenv PAGESIZE_DATA 4096 ; setenv PAGESIZE_TEXT 4096 ; setenv PAGESIZE_STACK 4096
systune -i ; percent_totalmem_4m_pages = 40 ; percent_totalmem_1m_pages = 7
systune -i ; percent_totalmem_256k_pages = 7 ; percent_totalmem_64k_pages = 7
limit stacksize 500000

```

The following is done before building each benchmark that requires (FEEDBACK):

```

rm -rf /tmp/SPEC2000 ; mkdir /tmp/SPEC2000 ; cd /tmp/SPEC2000 ; mkdir FBDIR_base ; mkdir FBDIR_peak

```