



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP 9000 Model L3000

SPECfp_rate2000 = 8.29

SPECfp_rate_base2000 = 7.66

SPEC license #: 3 | Tested by: HP Richardson, TX | Test date: Nov-2000 | Hardware Avail: Nov-2000 | Software Avail: Jan-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	511	7.27	2	417	8.90
171.swim	2	541	13.3	2	526	13.7
172.mgrid	2	465	8.99	2	465	8.99
173.applu	2	435	11.2	2	435	11.2
177.mesa	2	481	6.75	2	481	6.75
178.galgel	2	649	10.4	2	626	10.7
179.art	2	797	7.57	2	599	10.1
183.quake	2	626	4.82	2	443	6.81
187.facerec	2	855	5.16	2	852	5.17
188.amp	2	645	7.92	2	594	8.60
189.lucas	2	758	6.12	2	714	6.50
191.fma3d	2	924	5.27	2	924	5.27
200.sixtrack	2	400	6.38	2	355	7.19
301.apsi	2	522	11.5	2	552	10.9

Hardware

CPU: 550 MHz PA-8600
 CPU MHz: 550
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 1-4
 Parallel: No
 Primary Cache: 512KBI+1MBD (on chip)
 Secondary Cache: none
 L3 Cache: none
 Other Cache: None
 Memory: 8GB
 Disk Subsystem: 2x36 GB 10000RPM
 Other Hardware: --

Software

Operating System: HP-UX B.11.0
 Compiler: HP92453-01 A.11.01.20 HP C Compiler
 HP-UX f90 20001003 (213450) PHSS_22539 B.11.01.25
 HP MLIB Math Library B.07.00
 File System: HP-UX HFS
 System State: Multi-user

Notes/Tuning Information

Portability flags:
 178.galgel: +source=fixed
 188.amp: -DSPEC_CPU2000
 Compiler invoked in extended ANSI mode: cc -Ae
 Base flags:
 f90: +O3 +Onofltacc -Wl,-a,archive -Wl,+FPD
 cc: +Oall +Odataprefetch -Wl,-a,archive +I/+P
 Peak flags:
 Peak flags = base flags for 172.mgrid, 173.applu, 177.mesa and 191.fma3d
 168.wupwise: +O3 +Onofltacc +cat -Wl,+FPD -Wl,-a,archive
 171.swim: +O3 +Onolimit +Oinlinebudget=1000 -Wl,+FPD -Wl,-a,archive
 172.mgrid: basepeak
 173.applu: basepeak
 177.mesa: basepeak
 178.galgel: +Oall +fastallocatable -Wl,+FPD -Wl,-a,archive -llapack
 RM_SOURCES = lapak.f90
 179.art: +Oall +Odataprefetch +Onofltacc +Optrs_strongly_typed



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP 9000 Model L3000

SPECfp_rate2000 = 8.29
SPECfp_rate_base2000 = 7.66

SPEC license #: 3 Tested by: HP Richardson, TX Test date: Nov-2000 Hardware Avail: Nov-2000 Software Avail: Jan-2001

Notes/Tuning Information (Continued)

```

-Wl,+FPD -Wl,-a,archive +I/+P
183.quake: +Oall +Odataprefetch +Optrs_strongly_typed -Wl,+FPD -Wl,-a,archive
187.facerec: +O2 +Ofastaccess +fastallocatable -Wl,+FPD -Wl,-a,archive
-Wl,/opt/langtools/lib/fastmem.o
188.ampp: +Oall +Odataprefetch +Optrs_strongly_typed -Wl,+FPD
-Wl,-a,archive +I/+P
189.lucas: +O3 +Onoinline -Wl,+FPD -Wl,-a,archive
191.fma3d: basepeak
200.sixtrack: +O3 +Onoinline +Onolimit +Onolibcalls +Onodataprefetch -Wl,+FPD
-Wl,-a,archive -Wl,/opt/langtools/lib/fastmem.o
301.apsi: +O3 +Onodataprefetch +Onofltacc -Wl,+FPD -Wl,-a,archive
Kernel tunables:
vps_pagesize=4096, vps_ceiling=16384, maxdsiz=0X04000000, maxssiz=0X10000000, dbc_max_pct=10, dbc_min_pct=10
Unused processors disabled at boot
Event Monitoring System disabled.

```