



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER800/1000/2000 (563MHz)

SPECint2000 = 395
SPECint_base2000 = 363

SPEC license #: 19 Tested by: Fujitsu Limited Test date: Feb-2001 Hardware Avail: Feb-2001 Software Avail: Apr-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	100 200 300 400 500 600					
164.gzip	1400	409	343	409	343	[Bar chart showing ratio 343]					
175.vpr	1400	419	334	392	357	[Bar chart showing ratio 357]					
176.gcc	1100	369	298	302	364	[Bar chart showing ratio 364]					
181.mcf	1800	447	403	395	456	[Bar chart showing ratio 456]					
186.crafty	1000	263	380	236	424	[Bar chart showing ratio 424]					
197.parser	1800	480	375	479	376	[Bar chart showing ratio 376]					
252.eon	1300	327	398	303	429	[Bar chart showing ratio 429]					
253.perlbmk	1800	432	416	420	429	[Bar chart showing ratio 429]					
254.gap	1100	481	229	481	228	[Bar chart showing ratio 228]					
255.vortex	1900	333	570	322	589	[Bar chart showing ratio 589]					
256.bzip2	1500	409	367	401	374	[Bar chart showing ratio 374]					
300.twolf	3000	897	334	627	479	[Bar chart showing ratio 479]					

Hardware

CPU: SPARC64 GP
 CPU MHz: 563
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 4 to 16/4 to 32/8 to 128
 Parallel: None
 Primary Cache: 128KBI+128KBD on chip
 Secondary Cache: 8MB(I+D) off chip, per CPU
 L3 Cache: None
 Other Cache: None
 Memory: 8192MB
 Disk Subsystem: 1 x 18.2GB SCSI (10025rpm)
 Other Hardware: Ethernet

Software

Operating System: Solaris 8
 Compiler: Fujitsu Parallelnavi 1.0.1
 Sun Forte Developer 6 update 1
 File System: ufs
 System State: single user

Notes/Tuning Information

Baseline (except 252.eon, for Parallelnavi 1.0.1): -Kfast_GP=3,largepage

fdo_pre0=rm -rf `pwd`/*.*fbk

PASS1=-Kpg

PASS2=-Kpu=\$(EXEBASE).fbk

(252.eon, for Forte Developer 6 update 1): -fast -xcrossfile -xarch=v8plus

fdo_pre0=rm -rf `pwd`/../../feedback.profile `pwd`/SunWS_cache

PASS1=-xprofile=collect:`pwd`/../../feedback

PASS2=-xprofile=use:`pwd`/../../feedback

Peak (for Parallelnavi 1.0.1):

fdo_pre0=rm -rf `pwd`/*.*fbk

PASS1=-Kpg

PASS2=-Kpu=\$(EXEBASE).fbk

164.gzip: -Kfast_GP=3,largepage

175.vpr: -Kfast_GP=4,staticclump,memalias,switchopt,cond,GREG,nounroll,largepage,onefile,NOFLTLTD=3,xi=30

181.mcf: -Kfast_GP=2,nounroll,memalias,restp,prefetch=4,largepage -x-

186.crafty: -Kfast_GP=3,switchopt,cond,noiopt,staticclump,xi=6,memalias,largepage

197.parser: -Kfast_GP=3,switchopt,cond,staticclump,use_rodata,largepage,funcalign=128

253.perlbmk: -Kfast_GP=3,memalias,switchopt,largepage,bcopy

254.gap: -Kfast_GP=3,largepage

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER800/1000/2000 (563MHz)

SPECint2000 = 395
SPECint_base2000 = 363

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Feb-2001 | Hardware Avail: Feb-2001 | Software Avail: Apr-2001

Notes/Tuning Information (Continued)

```

256.bzip2: Kfast_GP=3,NOFLTLTD=1,use_rodata,staticclump,xi=8,cfunc,memalias,restp,largepage,funcalign=128
300.twolf: -Kfast_GP=5,GREG,popt,cfunc,staticclump,use_rodata,xi=10,nounroll,largepage,bcopy
(for Forte Developer 6 update 1)
fdo_pre0=rm -rf `pwd`/../feedback.profile `pwd`/SunWS_cache
PASS1=-xprofile=collect:`pwd`/../feedback
PASS2=-xprofile=use:`pwd`/../feedback
176.gcc: -fast -xcrossfile -W2,-whole -Wc,-Qgsched-trace_late=1,-Qgsched-T4,-Qiselect-funcalign=64
-xarch=v8plus -xprefetch
252.eon: -fast -xcrossfile -xregs=syst -xsafe=mem -Qoption iropt -Mt500,-restrict_g,-restrict
-Qoption cg -Qgsched-trace_late=1,-Qgsched-trace_spec_load=1,-Qgsched-T4 -xarch=v8plus
-lmopt
255.vortex: -fast -xsafe=mem -xcrossfile -W2,-Aheap,-reroll=1,-Aunroll,-Msl,-Mt500,-Mr6000,-crit
-Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=32 -Wc,-Qpeep-Sh0
-xrestrict -xdepend -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xarch=v8plus

```

Portability:

```

176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon: -library=iostream,no%Cstd
253.perlbnk: -DSPEC_CPU2000_SOLARIS -lnsl -lsocket
254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
-DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

```

Note:

System Tunables: (for /etc/system)

```

consistent_coloring=1, tune_t_fsflushr=86400, autoup=86400,
shmsys:shminfo_shmmax=268435456, shmsys:shminfo_shmmni=1024, shmsys:shminfo_shmseg=1024

```

(for /etc/opt/FJSVpnrmlpg.conf)

```

TSS=512M, SHMSEGSIZE=256M

```

ONESTEP=yes was set for all baseline and peak benchmarks.
Feedback directed optimization was used for all baseline and peak benchmarks.

Also used:

-Xa (base and peak, except where noted) for 176.gcc (base only), 181.mcf, 186.crafty, 197.parser (peak only), 254.gap
-dy (base) for all benchmarks except 252.eon, -dy (peak) for all except 176.gcc, 252.eon, 255. vortex
-DWANT_STD_PROTO for 181.mcf (base and peak), -DCPU2000 for 186.crafty (base and peak),
-DSUN -DCPU2000 for 197.parser (peak)

The flags listed above as "also used" were used for the actual compilation, but they had no effect (-D flags), were the compiler's default (-Xa), or the compiler's default when -Klargepage is used (-dy).

They are not necessary for result reproduction and can be omitted.