



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell  
Dell PowerEdge 7150

SPECfp\_rate2000 = --  
SPECfp\_rate\_base2000 = 8.16

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: May-2001 | Hardware Avail: Jul-2001 | Software Avail: Jun-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	272	6.84			
171.swim	1	226	15.9			
172.mgrid	1	240	8.69			
173.applu	1	205	11.9			
177.mesa	1	425	3.82			
178.galgel	1	286	11.8			
179.art	1	112	27.0			
183.quake	1	156	9.70			
187.facerec	1	298	7.40			
188.amp	1	428	5.96			
189.lucas	1	239	9.70			
191.fma3d	1	649	3.75			
200.sixtrack	1	192	6.66			
301.apsi	1	736	4.10			

### Hardware

CPU: Itanium processor (800 MHz)  
 CPU MHz: 800  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
 CPU(s) orderable: 1,2,4  
 Parallel: No  
 Primary Cache: 16KBI + 16KBD on chip  
 Secondary Cache: 96KB(I+D) on chip  
 L3 Cache: 4MB(I+D) off chip  
 Other Cache: N/A  
 Memory: 16 GB (64 x 256MB PC100 SDRAM)  
 Disk Subsystem: Seagate Ultra-2 SCSI  
 Other Hardware:

### Software

Operating System: Windows XP Advanced Server, 64-bit Edition (build 2479)  
 Compiler: Intel C++ and Fortran Compiler 5.0.1 Build 20010507  
 Microsoft Platform SDK (2462)  
 File System: NTFS  
 System State: Default

## Notes/Tuning Information

```

FEEDBACK-DIRECTED OPTIMIZATION
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
BASE TUNING
C: -Qipo -O3 +FDO
F77/F90: -Qipo -O3 -Qftz +FDO
PORTABILITY
178.galgel: -FI

```