



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 1000 Model 1600

SPECfp2000 = 288

SPECfp_base2000 = 260

SPEC license #: 6 Tested by: Sun Microsystems, Palo Alto Test date: Mar-2001 Hardware Avail: Sep-2000 Software Avail: Mar-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	515	311	515	311
171.swim	3100	1160	267	1154	269
172.mgrid	1800	995	181	990	182
173.applu	2100	1225	171	600	350
177.mesa	1400	462	303	458	305
178.galgel	2900	467	621	467	621
179.art	2600	388	671	333	782
183.quake	1300	807	161	761	171
187.facerec	1900	557	341	539	353
188.amp	2200	953	231	887	248
189.lucas	2000	1284	156	933	214
191.fma3d	2100	968	217	953	220
200.sixtrack	1100	596	185	596	185
301.apsi	2600	1016	256	969	268

Hardware

CPU: UltraSPARC-III
CPU MHz: 600
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1-2
Parallel: None
Primary Cache: 32KBI+64KBD on chip
Secondary Cache: 4MB(I+D) off chip
L3 Cache: None
Other Cache: None
Memory: 1GB
Disk Subsystem: 1 x 18GB
Other Hardware: --

Software

Operating System: Solaris 8 10/00
Compiler: Forte Developer 6 update 1 w/ latest patches
File System: UFS
System State: Single User

Notes/Tuning Information

Portability:

178.galgel: -e -fixed

Base C flags: -fast -xcrossfile -xprofile -xalias_level=std

Base F90 flags: -fast -xcrossfile -xprofile

Peak:

168.wupwise: basepeak=yes

171.swim: -fast -xchip=ultra2

172.mgrid: f77 -fast -xregs=syst

173.applu: f77 -fast -Qoption iropt -Adata_access, -Mt6000, -Mm12000, -Mr40000, -Ma400, -whole -xregs=syst

177.mesa: -fast -xcrossfile -xalias_level=strong -xprofile

178.galgel: basepeak=yes

179.art: -fast -xalias_level=strong -xdepend -xregs=syst -xprofile -dn -lmopt

183.quake: -fast -xalias_level=strong -xdepend -xprofile -lmopt

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 1000 Model 1600

SPECfp2000 =	288
SPECfp_base2000 =	260

SPEC license #:	6	Tested by:	Sun Microsystems, Palo Alto	Test date:	Mar-2001	Hardware Avail:	Sep-2000	Software Avail:	Mar-2001
-----------------	---	------------	-----------------------------	------------	----------	-----------------	----------	-----------------	----------

Notes/Tuning Information (Continued)

```
187.facerec: -fast -xcrossfile -stackvar -xprofile
188.ammf: -fast -xcrossfile -xalias_level=strong -xdepend -xregs=syst
        -W2,-whole -xprefetch -xprofile
189.lucas: -fast -qoption f90comp -array_pad_rows,1024 -Qoption iropt -whole -xprofile
191.fma3d: -fast -xcrossfile -stackvar -xprofile
200.sixtrack: -fast -xcrossfile -xprofile
301.apsi: -fast -qoption f90comp -expansion -xprofile
```

Note: ONESTEP=yes for all benchmarks.

Stack size set to unlimited by: ulimit -s unlimited

Forte Developer 6 update 1 patches include:

109503-07,109504-01,109505-08,109506-06,109508-01,109510-01,109513-06

Patch 111228-01 and obp 4.0.40 (or later) is required.

System configuration details located (as of June 2001) at
<http://www.sun.com/desktop/sunblade1000>