



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850GB motherboard (1.5 GHz, Pentium 4 processor)

SPECfp2000 = 615

SPECfp_base2000 = 606

SPEC license #: 13 Tested by: Intel Corporation Test date: Aug-2001 Hardware Avail: Nov-2000 Software Avail: Jun-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	202	793	201	796
171.swim	3100	246	1259	245	1266
172.mgrid	1800	311	579	297	606
173.applu	2100	306	687	300	700
177.mesa	1400	229	612	227	616
178.galgel	2900	370	784	368	787
179.art	2600	496	525	488	532
183.quake	1300	185	701	176	738
187.facerec	1900	279	681	282	675
188.amp	2200	613	359	605	364
189.lucas	2000	239	838	239	838
191.fma3d	2100	413	509	412	509
200.sixtrack	1100	399	275	384	287
301.apsi	2600	581	448	581	448

Hardware

CPU: Pentium 4 processor (1.5 GHz, 400 MHz bus)
CPU MHz: 1500
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 8KBD on chip
Secondary Cache: 256KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 256 MB (2 128 MB PC800 RDRAM non-ECC modules)
Disk Subsystem: IBM DTLA-307030 ATA-100
Other Hardware: None

Software

Operating System: Windows 2000(Build 2195, SP2)
Compiler: Intel C++ Compiler 5.0.1 Build 010525Z
Intel Fortran Compiler 5.0.1 Build 010525Z
Microsoft Visual C++ 6.0 SP5(for libraries)
MicroQuill SmartHeap library V6.0
File System: FAT32
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -Qipo -QxW -O3 +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW -O3 +FDO
171.swim: -Qipo -QxW -O3 +FDO
172.mgrid: -Qipo -QaxW -O3 +FDO
173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO
177.mesa: -Qipo -Oa -QxW -O3 +FDO
178.galgel: -Qipo -QxW -O3 +FDO
179.art: -Qipo -QxW -O3 -Oa +FDO
183.quake: -Qipo -QxW -Oa -Qrcd +FDO
187.facerec: -Qipo -QxW -O3 +FDO
187.facerec: LIBS=libIEPCF90.lib libintrins.lib libF90.lib
libqwin.lib libm.lib shlw32M.lib LIBC.lib
libirc.lib OLDNAMES.lib
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850GB motherboard (1.5 GHz, Pentium 4 processor)

SPECfp2000 = 615

SPECfp_base2000 = 606

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Aug-2001 | Hardware Avail: Nov-2000 | Software Avail: Jun-2001

Notes/Tuning Information (Continued)

188.ammp: -Qipo -QxW -O3 -Oa +FDO
189.lucas: -Qipo -QxW -O3 +FDO
191.fma3d: -Qipo -QxW -O3 +FDO
200.sixtrack: -Qipo -QxW +FDO
301.apsi: -Qipo -QxW -O3 +FDO

LIBS=libIEPCF90.lib libintrins.lib libF90.lib libqwind.lib libm.lib shlW32M.lib
LIBC.lib libirc.lib OLDNAMES.lib

shlW32M.lib is the SmartHeap library V6.0 from Microquill:

<http://www.microquill.com>

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 11/2000:

http://developer.intel.com/design/motherbd/gb/gb_ds.htm

Motherboard is available through Intel OEM Distribution Channel. See

<http://channel.intel.com/business/ibp/boards/d850gb.htm> for more information

The system bus runs at 400 MHz