



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 1000 Model 2900 Cu

SPECfp_rate2000 = 14.9
SPECfp_rate_base2000 = 12.6

SPEC license #: 6 Tested by: Sun Microsystems, Palo Alto Test date: Nov-2001 Hardware Avail: Dec-2001 Software Avail: Feb-2002

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	299	12.4	2	299	12.4
171.swim	2	555	13.0	2	555	13.0
172.mgrid	2	490	8.52	2	490	8.52
173.applu	2	861	5.66	2	404	12.1
177.mesa	2	297	10.9	2	289	11.2
178.galgel	2	205	32.8	2	164	41.1
179.art	2	31.8	190	2	31.8	190
183.equake	2	247	12.2	2	157	19.2
187.facerec	2	239	18.4	2	239	18.4
188.amp	2	519	9.83	2	506	10.1
189.lucas	2	963	4.82	2	493	9.41
191.fma3d	2	654	7.45	2	619	7.87
200.sixtrack	2	357	7.16	2	357	7.16
301.apsi	2	729	8.27	2	648	9.31

Hardware

CPU: UltraSPARC III Cu
 CPU MHz: 900
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
 CPU(s) orderable: 1-2
 Parallel: None
 Primary Cache: 32KBI+64KBD on chip
 Secondary Cache: 8MB(I+D) off chip
 L3 Cache: None
 Other Cache: None
 Memory: 2GB
 Disk Subsystem: 1 x 36GB
 Other Hardware: --

Software

Operating System: Solaris 8 10/01
 Compiler: Forte Developer 7 EA
 File System: tmpfs
 System State: Multi-User

Notes/Tuning Information

Portability:
 178.galgel: -e -fixed

Base Flags:
 Base C flags: -fast -xipo=2 -xalias_level=std -xprofile
 Base F90 flags: -fast -xcrossfile -lprism32 -xprofile

Peak Flags:
 168.wupwise: basepeak=yes
 171.swim: basepeak=yes
 172.mgrid: basepeak=yes
 173.applu: -fast -Qoption iropt -Adata_access,-Mt7000,-Mm14000,-Mr40000,-Ma400,-whole
 -xregs=syst -Qoption iropt -Rscalarrep,-MR -Qoption cg -Qlp=1-av=192-fa=1
 -Qoption f90comp -O3
 177.mesa: -fast -xcrossfile -xalias_level=strong -xprofile
 178.galgel: -fast -xcrossfile -xregs=syst -Qoption iropt -Addint:sf=9 -lsunperf -xprofile



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Blade 1000 Model 2900 Cu

SPECfp_rate2000 = 14.9
SPECfp_rate_base2000 = 12.6

SPEC license #: 6 Tested by: Sun Microsystems, Palo Alto Test date: Nov-2001 Hardware Avail: Dec-2001 Software Avail: Feb-2002

Notes/Tuning Information (Continued)

```

179.art: basepeak=yes
183.earthquake: -fast -xalias_level=strong -xdepend -W2,-whole,-Amemopt:arrayloc -xprefetch
                -Wc,-Qms_pipe-pref,-Qlp=1-av=256-t=4-fa=1-fl=1 -lprism32 -lmopt -xprofile
187.facerec: basepeak=yes
188.ammamp: -fast -xcrossfile -xalias_level=std -lprism32 -xprofile
189.lucas: -fast -Qoption f90comp -array_pad_rows,2002 -Qoption iropt -whole
            -xdepend -xprefetch -Qoption cg -Qms_pipe-pref,-Qlp=1-t=3-fa=1
            -lprism32 -xprofile
191.fma3d: -fast -xcrossfile -stackvar -xdepend -xprefetch
            -Qoption cg -Qlp=1-av=256-t=3-fa=1 -xprofile
200.sixtrack: basepeak=yes
301.apsi: -fast -Qoption iropt -Mt450 -lprism32 -xprofile

```

Forte Developer 7 (final) will ship May-2002

ONESTEP=yes for all benchmarks in peak and Fortran benchmarks in base

Shell Environments:

```

LD_LIBRARY_PATH=/usr/lib:/opt/fd7/lib/v8plusb:/opt/fd7/YNH/lib/v8plusb
PRISM_HEAP=268435456
PRISM_MODE=2

```

Stack size set to unlimited via "ulimit -s unlimited"

Kernel Parameters (/etc/system):

```

set shmsys:shminfo_shmmin=1
set shmsys:shminfo_shmmax=1477846784
set shmsys:shminfo_shmmni=256
set shmsys:shminfo_shmseg=400

```

System configuration details located (as of Dec 2001) at
<http://www.sun.com/desktop/products/ws.html>