



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V880

SPECfp_rate2000 = 31.2
SPECfp_rate_base2000 = 29.0

SPEC license #: 6 Tested by: Sun Microsystems, Palo Alto Test date: Nov-2001 Hardware Avail: Oct-2001 Software Avail: Feb-2002

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	543	27.4	8	543	27.4
171.swim	8	2295	12.5	8	2295	12.5
172.mgrid	8	1092	15.3	8	1092	15.3
173.applu	8	1492	13.1	8	640	30.4
177.mesa	8	366	35.5	8	361	35.9
178.galgel	8	387	69.6	8	313	85.9
179.art	8	93.9	257	8	93.9	257
183.quake	8	474	25.5	8	506	23.8
187.facerec	8	340	51.8	8	340	51.8
188.amp	8	725	28.1	8	752	27.2
189.lucas	8	1056	17.6	8	1319	14.1
191.fma3d	8	1137	17.1	8	1030	18.9
200.sixtrack	8	429	23.8	8	429	23.8
301.apsi	8	920	26.2	8	783	30.8

Hardware

CPU: UltraSPARC III
CPU MHz: 750
FPU: Integrated
CPU(s) enabled: 8 cores, 8 chips, 1 core/chip
CPU(s) orderable: 2,4,6,8
Parallel: None
Primary Cache: 32KBI+64KBD on chip
Secondary Cache: 8MB(I+D) off chip
L3 Cache: None
Other Cache: None
Memory: 16GB
Disk Subsystem: 9 x 18GB
Other Hardware: --

Software

Operating System: Solaris 8 7/01
Compiler: Forte Developer 7 EA
Forte Developer 6 update 2
File System: tmpfs
System State: Multi-User

Notes/Tuning Information

Portability:
178.galgel: -e -fixed

Base Flags:
Base C flags: -fast -xipo=2 -xalias_level=std -xprofile
Base F90 flags: -fast -xcrossfile -lprism32 -xprofile

Peak Flags:
168.wupwise: basepeak=yes
171.swim: basepeak=yes
172.mgrid: basepeak=yes
173.applu: -fast -Qoption iropt -Adata_access,-Mt7000,-Mm14000,-Mr40000,-Ma400,-whole
-xregs=syst -Qoption iropt -Rscalarrep,-MR -Qoption cg -Qlp=1-av=192-fa=1
-Qoption f90comp -O3
177.mesa: -fast -xcrossfile -xalias_level=strong -xprofile
178.galgel: -fast -xcrossfile -xregs=syst -Qoption iropt -Addint:sf=9 -lsunperf -xprofile



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V880

SPECfp_rate2000 = 31.2
SPECfp_rate_base2000 = 29.0

SPEC license #: 6 Tested by: Sun Microsystems, Palo Alto Test date: Nov-2001 Hardware Avail: Oct-2001 Software Avail: Feb-2002

Notes/Tuning Information (Continued)

```
179.art: basepeak=yes
183.earthquake: -fast -xalias_level=strong -xdepend -W2,-whole,-Amemopt:arrayloc -xprefetch
                -Wc,-Qms_pipe-pref,-Qlp=1-av=256-t=4-fa=1-fl=1 -lprism32 -lmopt -xprofile
187.facerec: basepeak=yes
188.amm: -fast -xcrossfile -xalias_level=std -lprism32 -xprofile
189.lucas: -fast -Qoption f90comp -array_pad_rows,2002 -Qoption iropt -whole
           -xdepend -xprefetch -Qoption cg -Qms_pipe-pref,-Qlp=1-t=3-fa=1
           -lprism32 -xprofile
191.fma3d: -fast -xcrossfile -stackvar -xdepend -xprefetch
           -Qoption cg -Qlp=1-av=256-t=3-fa=1 -xprofile
200.sixtrack: basepeak=yes
301.apsi: -fast -Qoption iropt -Mt450 -lprism32 -xprofile
```

Forte Developer 7 (final) will ship May-2002

ONESTEP=yes for all benchmarks in base and peak except for C benchmarks in fp base

Shell Environments:

```
LD_LIBRARY_PATH=/usr/lib:/ForteD7/FD7/lib/v8plusb:/ForteD7/FD7/YNH/lib/v8plusb
PRISM_HEAP=268435456
PRISM_MODE=2
```

Stack size set to unlimited via "ulimit -s unlimited"

Kernel Parameters (/etc/system):

```
set shmsys:shminfo_shmmin=1
set shmsys:shminfo_shmmax=1477846784
set shmsys:shminfo_shmmni=256
set shmsys:shminfo_shmseg=400
```

System configuration details located at

<http://www.sun.com/servers/workgroup/880/>