



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**SGI**  
SGI Origin 3800 128X 500MHz R14k

SPECint\_rate2000 = **605**  
SPECint\_rate\_base2000 = **582**

SPEC license #: 4 | Tested by: SGI | Test date: Nov-2001 | Hardware Avail: Jul-2001 | Software Avail: Nov-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	128	530	392	128	510	408
175.vpr	128	305	681	128	297	701
176.gcc	128	302	542	128	300	544
181.mcf	128	283	943	128	283	943
186.crafty	128	257	577	128	250	594
197.parser	128	542	493	128	516	518
252.eon	128	308	627	128	288	670
253.perlbnk	128	613	436	128	605	441
254.gap	128	437	374	128	437	374
255.vortex	128	343	823	128	295	956
256.bzip2	128	375	594	128	346	643
300.twolf	128	570	782	128	570	782

Hardware	Software
CPU: R14000	Operating System: IRIX 6.5.14m
CPU MHz: 500	Compiler: MIPSpro 7.3.1.2m C, C++
FPU: Integrated	SCSL 1.4 Math Library
CPU(s) enabled: 128 cores, 128 chips, 1 core/chip	File System: xfs
CPU(s) orderable: 4-512	System State: Single-user
Parallel: No	
Primary Cache: 32KBI + 32KBD on chip	
Secondary Cache: 8MB(I+D) off chip	
L3 Cache: N/A	
Other Cache: N/A	
Memory: 128 GB	
Disk Subsystem: 1 x 18 GB FC, 4 x 18 GB FC (striped)	
Other Hardware: None	

## Notes/Tuning Information

Baseline optimization flags (C and C++ use same flags):  
 PASS1 : -Ofast=ip27 -IPA:use\_intrinsic -fb\_create /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)  
 PASS2 : -Ofast=ip27 -IPA:use\_intrinsic -fb\_opt /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)

Portability Flags:  
 176.gcc: -Dalloca=\_\_builtin\_alloca -DMIPS -DHOST\_WORDS\_BIG\_ENDIAN  
 186.crafty: -DSGI  
 252.eon: -lm  
 253.perlbnk: -DSPEC\_CPU2000\_SGI -DI\_FCNTL  
 254.gap: -DSYS\_IS\_USG -DSYS\_HAS\_TIME\_PROTO -DSYS\_HAS\_SIGNAL\_PROTO -DSYS\_HAS\_IOCTL\_PROTO  
           -DSYS\_HAS\_ANSI -DSYS\_HAS\_CALLOC\_PROTO  
 300.twolf: -DHAVE\_SIGNED\_CHAR

Peak optimization flags:  
 note: all occurrences of (FEEDBACK) below means compiled with a two-step process:  
 PASS1 = -fb\_create /tmp/SPEC2000/FBDIR\_peak/\$(EXEBASE)  
 PASS2 = -fb\_opt /tmp/SPEC2000/FBDIR\_peak/\$(EXEBASE)  
 164.gzip: -Ofast=ip27 -IPA:space=500:plimit=500 -lmalloc (FEEDBACK)  
 175.vpr: -Ofast=ip27 -IPA:space=300:plimit=10000:callee\_limit=5000:linear=on  
 . -LNO:prefetch Ahead=2 -INLINE:aggressive=on  
 . -OPT:Olimit=0:alias=disjoint:alias=restrict -CG:ld\_latency=10 -lmalloc (FEEDBACK)  
 181.mcf: basepeak=yes



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI

SGI Origin 3800 128X 500MHz R14k

SPECint\_rate2000 = 605

SPECint\_rate\_base2000 = 582

SPEC license #: 4 | Tested by: SGI | Test date: Nov-2001 | Hardware Avail: Jul-2001 | Software Avail: Nov-2001

## Notes/Tuning Information (Continued)

```

176.gcc: -Ofast=ip27 -CG:ld_latency=4 (FEEDBACK)
186.crafty: -Ofast=ip27 -LNO:prefetch=0 -OPT:goto=off -CG:ld_latency=4 -lmalloc (FEEDBACK)
197.parser: -Ofast=ip27 -IPA:min_hot=14 (FEEDBACK)
252.eon: -Ofast=ip27 -LNO:prefetch=0 -LANG:exceptions=off -CG:ld_latency=4 -lmalloc -lm
      (FEEDBACK)
253.perlbnk: -Ofast=ip27 -IPA:use_intrinsic -Wl,-x (FEEDBACK)
254.gap: -Ofast=ip27 -IPA:use_intrinsic -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4
      -OPT:alias=restrict:alias=disjoint -IPA:min_hot=7 -CG:ld_latency=8 -lmalloc (FEEDBACK)
255.vortex: -Ofast=ip27 -IPA:use_intrinsic
      -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4 -LNO:opt=0 -CG:ld_latency=5
      -IPA:min_hot=14 -TENV:X=4 -IPA:space=500:plimit=3600 -OPT:goto=off (FEEDBACK)
256.bzip2: -Ofast=ip27 -IPA:min_hot=5:space=500:plimit=2900 -INLINE:aggressive=on (FEEDBACK)
300.twolf: basepeak=yes

```

The following O/S parameters were set:

```

setenv PAGESIZE_DATA 4096 ; setenv PAGESIZE_TEXT 4096 ; setenv PAGESIZE_STACK 4096
system -i ; percent_totalmem_4m_pages = 40 ; percent_totalmem_1m_pages = 7
system -i ; percent_totalmem_256k_pages = 7 ; percent_totalmem_64k_pages = 7
system -i ; r12k_bdiag = 0x4000000 ;
limit stacksize 500000

```

The following is done before building each benchmark that requires (FEEDBACK):

```

rm -rf /tmp/SPEC2000 ; mkdir /tmp/SPEC2000 ; cd /tmp/SPEC2000 ; mkdir FBDIR_base ; mkdir FBDIR_peak
The first disk mentioned in the Disk Subsystem is the system disk. A striped
XFS filesystem was created using the rest of the disks and the benchmark was
run on this.

```

Jobs are submitted using dplace. Contents of the placement file submit.pf:  
 memories 1 in topology physical near \$NODE threads 1 run thread 0 on memory  
 0 using cpu \$CPU