



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation
RS/6000 SP-450MHz T/W(1 CPU)

SPECfp2000 = 433

SPECfp_base2000 = 426

SPEC license #: 11 Tested by: IBM Corp. Test date: Sep-2001 Hardware Avail: Jan-2002 Software Avail: Dec-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	277	577	277	577
171.swim	3100	772	402	772	402
172.mgrid	1800	546	330	546	330
173.applu	2100	651	323	648	324
177.mesa	1400	432	324	420	333
178.galgel	2900	303	958	303	958
179.art	2600	242	1074	240	1084
183.earthquake	1300	248	524	228	571
187.facerec	1900	417	455	417	455
188.amp	2200	603	365	588	374
189.lucas	2000	704	284	681	294
191.fma3d	2100	598	351	584	359
200.sixtrack	1100	432	255	432	255
301.apsi	2600	718	362	718	362

Hardware

CPU: POWER3-II
CPU MHz: 450
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 2,4
Parallel: No
Primary Cache: 32KBI+64KBD (on chip)
Secondary Cache: 8MB unified (off chip)
L3 Cache: None
Other Cache: None
Memory: 2GB
Disk Subsystem: 2x18GB 10000RPM
Other Hardware: None

Software

Operating System: AIX 5L V5.1
Compiler: Fortran 77 and 90: IBM xl Fortran 7.1.1.0 invoked as xlf90 for Fortran 90 and as xlf for Fortran 77
C: IBM VAC++ 5.0.2.0 invoked as xlc
File System: AIX/JFS
System State: Multi-user

Notes/Tuning Information

Portability Flags

-qfixed used in: wupwise, swim, mgrid, applu, galgel, sixtrack, apsi
-qsuffix=f=f90 used in: galgel, facerec, lucas, fma3d

Base Optimization Flags:

Fortran: -O5 -lmass
C: -O5 -lmass

Peak Optimization Flags

168.wupwise: (basepeak=1)
171.swim: (basepeak=1)
172.mgrid: (basepeak=1)
173.applu: -O5 -lmass -qipa=partition=large
177.mesa: -O5 -lmass -qipa=partition=large, fdpr -v -R3
178.galgel: (basepeak=1)
179.art: -O5 -lmass -qalign=natural
183.earthquake: -O5 -lmass -lhmu -qinline
187.facerec: (basepeak=1)
188.amp: -O3 -qarch=pwr3



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation
RS/6000 SP-450MHz T/W(1 CPU)

SPECfp2000 = 433
SPECfp_base2000 = 426

SPEC license #: 11 | Tested by: IBM Corp. | Test date: Sep-2001 | Hardware Avail: Jan-2002 | Software Avail: Dec-2001

Notes/Tuning Information (Continued)

```
189.lucas: -qpdf1/pdf2 -O3 -lhm -lmas
           -qipa=partition=large, fdpr -v -R3
191.fma3d: -O4 -lmas -qipa=partition=large
200.sixtrack: (basepeak=1)
301.apsi: (basepeak=1)
fpdr: Feedback directed program restructuring tool
/usr/spec2000 filesystem mounted with no JFS log file I/O
APAR IY 21957 was applied to AIX 5L V5.1 to enable new hardware support
```