



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER800/1000/2000 (788MHz)

SPECfp2000 = **551**
SPECfp_base2000 = **420**

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Jun-2002 | Hardware Avail: Aug-2002 | Software Avail: May-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	540	296	308	519
171.swim	3100	876	354	824	376
172.mgrid	1800	615	293	563	320
173.applu	2100	1035	203	448	469
177.mesa	1400	476	294	307	456
178.galgel	2900	270	1075	197	1469
179.art	2600	84.2	3086	75.3	3453
183.earthquake	1300	343	379	177	735
187.facerec	1900	308	617	280	679
188.amp	2200	544	405	405	543
189.lucas	2000	622	322	622	322
191.fma3d	2100	748	281	747	281
200.sixtrack	1100	412	267	299	367
301.apsi	2600	675	385	660	394

Hardware

CPU: SPARC64 GP
CPU MHz: 788
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 4 to 16/4 to 32/8 to 128
Parallel: None
Primary Cache: 128KBI+128KBD on chip
Secondary Cache: 8MB(I+D) off chip, per CPU
L3 Cache: None
Other Cache: None
Memory: 8192MB
Disk Subsystem: 1 x 18.2GB SCSI (10025rpm)
Other Hardware: Ethernet

Software

Operating System: Solaris 8 2/02 with patches 108434-07 and 108435-07.
Compiler: Fujitsu Parallelnavi 1.0.2 with patches 911403-01 and 911746-01, Sun ONE Studio 7 with patches 111704-01, 111705-01, 111706-01, 111708-01, 111709-01, 111715-01 and 111716-01, Sun Performance Library 7
File System: ufs
System State: single user

Notes/Tuning Information

```
FDO: (Parallelnavi 1.0.2)
fdo_pre0=rm -rf `pwd`/*.*.d
PASS1=-Kpg PASS2=-Kpu
FDO: (Sun ONE Studio 7)
fdo_pre0=rm -rf `pwd`/../feedback.profile
PASS1=-xprofile=collect:`pwd`/../feedback
PASS2=-xprofile=use:`pwd`/../feedback
Baseline :
(using Fortran compiler of Sun ONE Studio 7)
-fast -xtarget=ultra3 -lprism32 FDO

(using C compiler of Sun ONE Studio 7)
-fast -xipo=2 -xdepend FDO

Peak:
(using Fortran compiler of Parallelnavi 1.0.2)
168.wupwise: -Kfast_GP=2,prefetch=4,nounroll -x dir=`pwd`/../../src
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER800/1000/2000 (788MHz)

SPECfp2000 = 551
SPECfp_base2000 = 420

SPEC license #: 19 Tested by: Fujitsu Limited Test date: Jun-2002 Hardware Avail: Aug-2002 Software Avail: May-2002

Notes/Tuning Information (Continued)

-fs -lssl2mtfma FDO ONESTEP=yes

171.swim: -Kfast_GP=2,GREG,preex,ilfunc,prefetch=3,largepage,commonpad=152,prefetch_iteration=3,unroll=2,nogs,frecipro
-O4 -fs

172.mgrid: -Kfast_GP=2,preex,GREG,commonpad=144,unroll=3,largepage,prefetch=3
-O4 -fs

178.galgel: -Kfast_GP=2,GREG,largepage,preex,unroll=3,prefetch_iteration=2,commonpad=24
-O4 -lssl2mtfma -fs FDO

RM_SOURCES=lapak.f90

200.sixtrack: -Kfast_GP=2,GREG,noprefetch,unroll=4,largepage,frecipro -fs

301.apsi: -Kfast_GP=2,GREG,preex,ilfunc,largepage,unroll=2 -O4 -fs

(using FORTRAN77 compiler of Sun ONE Studio 7)

173.applu: -fast -xtarget=ultra3 -Qoption iropt -Adata_access,-Mt7000,-Mm14000,-Mr40000,-Ma400,-whole
-xregs=syst -Qoption iropt -Rscalarrep,-MR -Qoption cg
-Qlp=1-av=192-fa=1 -Qoption f90comp -O3 -stackvar ONESTEP=yes

(using FORTRAN90 compiler of Sun ONE Studio 7)

187.facerec: -fast -xarch=v9 FDO ONESTEP=yes

189.lucas: basepeak=1

191.fma3d: -fast -xarch=v8plusb -xcrossfile -stackvar -xdepend
-xprefetch -Qoption cg -Qlp=1-av=256-t=3-fa=1 FDO ONESTEP=yes

(using C compiler of Sun ONE Studio 7)

177.mesa: -fast -xtarget=ultra2 -xcrossfile -xrestrict -xalias_level=strong
-xregs=syst -Wc,-Qgsched-trace_late=1,-Qgsched-trace_spec_load=1
-xarch=v8plus -W2,-Amemopt -xsafe=mem -dn
FDO ONESTEP=yes

179.art: -fast -xtarget=ultra3 -xipo=2 -xalias_level=strong -xregs=syst -dn
FDO ONESTEP=yes

183.quake: -fast -xtarget=ultra3 -xalias_level=std -xdepend
-W2,-whole,-Amemopt:arrayloc,-crit -xprefetch -Wc,-Qms_pipe-pref,-Qlp=1-av=256-t=4-fa=1-fl=1 -lprism32 -lmopt -lm
FDO ONESTEP=yes

188.ammp: -fast -xtarget=ultra3 -xcrossfile -xrestrict
-xalias_level=strong -xdepend -xprefetch
-Wc,-Qiselect-funcalign=64 -lprism32 FDO ONESTEP=yes

Portability:

(for Sun ONE Studio 7)

178.galgel: -e -fixed

(for Parallelnavi 1.0.2)

178.galgel: -Am -Fixed

Note:

System Tunables: (for /etc/system)

consistent_coloring=1, tune_t_fsflushr=86400, autoup=86400,

shmsys:shminfo_shmmax=1477846784, shmsys:shminfo_shmnni=1024, shmsys:shminfo_shmseg=1024,shminfo_shmmin=1

(for /etc/opt/FJSVpnm/lpg.conf)

TSS=512M, SHMSEGSIZE=256M

Shell Environments:

LD_LIBRARY_PATH="/usr/lib:/opt/FD7/SUNWspro/lib/v8plusb:/opt/FD7/SUNWspro/prod/lib/v8plusb:/opt/FSUNf90/lib"

LD_LIBRARY_PATH_64="/usr/lib/64:/opt/FD7/SUNWspro/lib/v9:/opt/FD7/SUNWspro/prod/lib/v9"

PRISM_HEAP=268435456

PRISM_MODE=2

Feedback directed optimization was used for all baseline benchmarks and peak benchmarks except following peak benchmarks: 171.swim, 172.mgrid, 173.applu, 200.sixtrack.

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEPOWER800/1000/2000 (788MHz)

SPECfp2000 =	551
SPECfp_base2000 =	420

SPEC license #:	19	Tested by:	Fujitsu Limited	Test date:	Jun-2002	Hardware Avail:	Aug-2002	Software Avail:	May-2002
-----------------	----	------------	-----------------	------------	----------	-----------------	----------	-----------------	----------

Notes/Tuning Information (Continued)

System board used with only one CPU present.