



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**Fujitsu Limited**  
**PRIMEPOWER200 (700MHz)**

SPECfp2000 = **505**

SPECfp\_base2000 = **393**

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Jun-2002 | Hardware Avail: Aug-2002 | Software Avail: May-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	462	346	339	472
171.swim	3100	860	361	823	377
172.mgrid	1800	653	276	562	320
173.applu	2100	1012	207	476	442
177.mesa	1400	538	260	351	399
178.galgel	2900	306	948	217	1334
179.art	2600	95.0	2738	69.1	3765
183.earth	1300	386	337	242	537
187.facerec	1900	366	520	336	566
188.amp	2200	614	358	488	450
189.lucas	2000	605	331	605	331
191.fma3d	2100	835	251	826	254
200.sixtrack	1100	468	235	341	323
301.apsi	2600	735	354	693	375

### Hardware

CPU: SPARC64 GP  
CPU MHz: 700  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
CPU(s) orderable: 1 to 2  
Parallel: None  
Primary Cache: 128KBI+128KBD on chip  
Secondary Cache: 8MB(I+D) off chip, per CPU  
L3 Cache: None  
Other Cache: None  
Memory: 4096MB  
Disk Subsystem: 1 x 36.4GB SCSI (10000rpm)  
Other Hardware: Ethernet

### Software

Operating System: Solaris 8 2/02 with patches 108434-07 and 108435-07.  
Compiler: Fujitsu Parallelnavi 1.0.2 with patches 911403-01 and 911746-01, Sun ONE Studio 7 with patches 111704-01, 111705-01, 111706-01, 111708-01, 111709-01, 111715-01 and 111716-01, Sun Performance Library 7  
File System: ufs  
System State: single user

## Notes/Tuning Information

```
FDO: (Parallelnavi 1.0.2)
fdo_pre0=rm -rf `pwd`/*.*.d
PASS1=-Kpg PASS2=-Kpu
FDO: (Sun ONE Studio 7)
fdo_pre0=rm -rf `pwd`/../feedback.profile
PASS1=-xprofile=collect:`pwd`/../feedback
PASS2=-xprofile=use:`pwd`/../feedback
Baseline :
(using Fortran compiler of Sun ONE Studio 7)
-fast -xtarget=ultra3 -lprism32 FDO

(using C compiler of Sun ONE Studio 7)
-fast -xipo=2 -xdepend FDO

Peak:
(using FORTRAN77 compiler of Sun ONE Studio 7)
168.wupwise: -fast -xtarget=ultra3 -xarch=v8plus -xipo=2 -xlic_lib=sunperf -lprism32 FDO ONESTEP=yes
```



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**Fujitsu Limited**  
**PRIMEPOWER200 (700MHz)**

SPECfp2000 = **505**  
SPECfp\_base2000 = **393**

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Jun-2002 | Hardware Avail: Aug-2002 | Software Avail: May-2002

## Notes/Tuning Information (Continued)

173.applu: -fast -xtarget=ultra3 -Qoption iropt -Adata\_access,-Mt7000,-Mm14000,-Mr40000,-Ma400,-whole  
-xregs=syst -Qoption iropt -Rscalarrep,-MR -Qoption cg -Qlp=1-av=192-fa=1 -Qoption f90comp -O3 -stackvar  
ONESTEP=yes

(using FORTRAN90 compiler of Sun ONE Studio 7)

187.facerec: -fast -xarch=v9 FDO ONESTEP=yes  
189.lucas: basepeak=yes  
191.fma3d: -fast -xarch=v8plusb -xcrossfile -stackvar -xdepend  
-xprefetch -Qoption cg -Qlp=1-av=256-t=3-fa=1 FDO ONESTEP=yes

(using Fortran compiler of Parallelnavi 1.0.2)

171.swim: -Kfast\_GP=2,GREG,preex,ilfunc,prefetch=3,largepage,commonpad=152,prefetch\_iteration=3,unroll=2,nogs,frecipro  
-O4 -fs  
172.mgrid: -Kfast\_GP=2,preex,GREG,commonpad=144,unroll=3,prefetch=3  
-O4 -fs  
178.galgel: -Kfast\_GP=2,GREG,largepage,preex,unroll=3,prefetch\_iteration=2,commonpad=24 -O4 -lssl2mtfma -fs  
FDO RM\_SOURCES=lapak.f90  
200.sixtrack: -Kfast\_GP=2,GREG,noprefetch,unroll=4,largepage,frecipro -fs  
301.apsi: -Kfast\_GP=2,GREG,preex,ilfunc,largepage,unroll=2 -O4 -fs

(using C compiler of Sun ONE Studio 7)

177.mesa: -fast -xtarget=ultra2 -xcrossfile -xrestrict -xalias\_level=strong -xregs=syst  
-Wc,-Qgsched-trace\_late=1,-Qgsched-trace\_spec\_load=1 -xarch=v8plus -W2,-Amemopt -xsafe=mem -dn  
FDO ONESTEP=yes  
179.art: -fast -xtarget=ultra3 -xipo=2 -xalias\_level=strong -xregs=syst -dn  
FDO ONESTEP=yes  
183.equake: -fast -xtarget=ultra3 -xalias\_level=std -xdepend -W2,-whole,-Amemopt:arrayloc,-crit  
-xprefetch -Wc,-Qms\_pipe-pref,-Qlp=1-av=256-t=4-fa=1-fl=1 -lprism32 -lmopt -lm  
FDO ONESTEP=yes  
188.ammp: -fast -xtarget=ultra3 -xcrossfile -xrestrict  
-xalias\_level=strong -xdepend -xprefetch  
-Wc,-Qiselect-funcalign=64 -lprism32 FDO ONESTEP=yes

### Portability:

(for Sun ONE Studio 7)  
178.galgel: -e -fixed  
(for Parallelnavi 1.0.2)  
178.galgel: -Am -Fixed

### Note:

System Tunables: (for /etc/system)  
consistent\_coloring=1, tune\_t\_fsflushr=86400, autoup=86400,  
shmsys:shminfo\_shmmax=1477846784, shmsys:shminfo\_shmni=1024, shmsys:shminfo\_shmseg=1024,shminfo\_shmmin=1  
(for /etc/opt/FJSVpnm/lpg.conf)  
TSS=2G, SHMSEGSIZE=256M

### Shell Environments:

LD\_LIBRARY\_PATH="/usr/lib:/opt/SUNWspro/lib/v8plusb:/opt/SUNWspro/prod/lib/v8plusb:/opt/FSUNf90/lib"  
LD\_LIBRARY\_PATH\_64="/usr/lib/64:/opt/SUNWspro/lib/v9:/opt/SUNWspro/prod/lib/v9"  
PRISM\_HEAP=268435456  
PRISM\_MODE=2

Feedback directed optimization was used for all baseline benchmarks and peak benchmarks  
except following peak benchmarks: 171.swim, 172.mgrid, 173.applu, 200.sixtrack.  
System board used with only one CPU present.