



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMV2 motherboard (2.53 GHz, Pentium 4 processor)

SPECint2000 = 914

SPECint_base2000 = 910

SPEC license #: 13 Tested by: Intel Corporation Test date: May-2002 Hardware Avail: May-2002 Software Avail: Apr-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	500 1000 1500 2000			
164.gzip	1400	134	1048	133	1049	[Bar chart showing ratio 1049]			
175.vpr	1400	250	560	250	560	[Bar chart showing ratio 560]			
176.gcc	1100	100	1097	101	1094	[Bar chart showing ratio 1094]			
181.mcf	1800	291	619	291	618	[Bar chart showing ratio 618]			
186.crafty	1000	103	969	104	962	[Bar chart showing ratio 962]			
197.parser	1800	206	876	206	875	[Bar chart showing ratio 875]			
252.eon	1300	120	1080	112	1159	[Bar chart showing ratio 1159]			
253.perlbmk	1800	158	1138	158	1137	[Bar chart showing ratio 1137]			
254.gap	1100	92.2	1193	92.2	1193	[Bar chart showing ratio 1193]			
255.vortex	1900	123	1541	124	1531	[Bar chart showing ratio 1531]			
256.bzip2	1500	210	715	209	717	[Bar chart showing ratio 717]			
300.twolf	3000	508	590	510	589	[Bar chart showing ratio 589]			

Hardware

CPU: Pentium 4 processor (2.53 GHz, 533 MHz bus)
CPU MHz: 2533
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 8KBD on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 256 MB (2 128 MB PC800-40 RDRAM non-ECC modules)
Disk Subsystem: IBM 120GXP 80 GB IC35L080AVVA07-0 ATA-100
Other Hardware: None

Software

Operating System: Windows XP Professional(Build 2600)
Compiler: Intel C++ Compiler 6.0 Build 020321Z
Intel Fortran Compiler 6.0 Build 020321Z
Microsoft Visual C++ 6.0 SP5(for libraries)
File System: FAT32
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning for C programs: -QxW -Qipo -O3 +FDO

Base tuning for C++ programs: -QxW -Qipo -GX -GR

Portability flags:

176.gcc: -Dalloca=_alloca /F10000000

186.crafty: -DNT_i386

253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT

254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Peak tuning:

164.gzip: -QxW -Qipo -Oa -O3 +FDO

175.vpr: -QxW -Qwp_ipo -O3 +FDO

176.gcc: -QxW -Qipo -O3 +FDO

181.mcf: -QxW -Qipo -O3 +FDO

186.crafty: -QxW -Qipo -Oa -O3 +FDO

197.parser: -QxW -Qipo -O3 +FDO

252.eon: -QxW -Qipo -O3 +FDO

253.perlbmk: -QxW -Qipo -O3 +FDO

254.gap: -QxW -Qipo -O3 +FDO

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 8/2002:

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMV2 motherboard (2.53 GHz, Pentium 4 processor)

SPECint2000 = 914

SPECint_base2000 = 910

SPEC license #: 13 | Tested by: Intel Corporation | Test date: May-2002 | Hardware Avail: May-2002 | Software Avail: Apr-2002

Notes/Tuning Information (Continued)

<http://developer.intel.com/design/motherbd/mv2/index.htm>

Motherboard ordering information is available at:

<http://program.intel.com/shared/products/boards/d850emv2/index.htm>

The system bus runs at 533 MHz