



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMVR motherboard (2.4 GHz, Pentium 4 processor)

SPECint2000 = 927

SPECint_base2000 = 922

SPEC license #: 13 Tested by: Intel Corporation Test date: Jul-2002 Hardware Avail: Oct-2002 Software Avail: Apr-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	141	996	140	1000	
175.vpr	1400	236	593	236	592	
176.gcc	1100	99.0	1111	98.7	1115	
181.mcf	1800	248	725	248	725	
186.crafty	1000	108	929	109	921	
197.parser	1800	205	880	205	880	
252.eon	1300	127	1023	118	1099	
253.perlbmk	1800	165	1093	165	1093	
254.gap	1100	92.1	1194	92.2	1194	
255.vortex	1900	123	1549	123	1540	
256.bzip2	1500	203	740	202	744	
300.twolf	3000	474	633	473	634	

Hardware

CPU: Pentium 4 processor (2.4 GHz, 533 MHz bus)
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 12k micro-ops I + 8KBD on chip
 Secondary Cache: 512KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 256 MB (2 128 MB PC1066-32 RDRAM non-ECC modules)
 Disk Subsystem: IBM 120GXP 80 GB IC35L080AVVA07-0 ATA-100
 Other Hardware: None

Software

Operating System: Windows XP Professional(Build 2600)
 Compiler: Intel C++ Compiler 6.0 Build 020321Z
 Intel Fortran Compiler 6.0 Build 020321Z
 Microsoft Visual C++ 6.0 SP5(for libraries)
 File System: FAT32
 System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning for C programs: -QxW -Qipo -O3 +FDO

Base tuning for C++ programs: -QxW -Qipo -GX -GR

Portability flags:

176.gcc: -Dalloca=_alloca /F10000000

186.crafty: -DNT_i386

253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT

254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Peak tuning:

164.gzip: -QxW -Qipo -Oa -O3 +FDO

175.vpr: -QxW -Qwp_ipo -O3 +FDO

176.gcc: -QxW -Qipo -O3 +FDO

181.mcf: -QxW -Qipo -O3 +FDO

186.crafty: -QxW -Qipo -Oa -O3 +FDO

197.parser: -QxW -Qipo -O3 +FDO

252.eon: -QxW -Qipo -O3 +FDO

253.perlbmk: -QxW -Qipo -O3 +FDO

254.gap: -QxW -Qipo -O3 +FDO

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 10/2002:

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMVR motherboard (2.4 GHz, Pentium 4 processor)

SPECint2000 = 927

SPECint_base2000 = 922

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jul-2002 | Hardware Avail: Oct-2002 | Software Avail: Apr-2002

Notes/Tuning Information (Continued)

<http://developer.intel.com/design/motherbd/mv2/index.htm>

Motherboard ordering information is available at:

<http://program.intel.com/shared/products/boards/d850emv2/index.htm>

The system bus runs at 533 MHz