



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**Dell**  
Precision WorkStation 350 (2.53 GHz P4)

SPECint\_rate2000 = 11.4  
SPECint\_rate\_base2000 = 11.0

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Nov-2002 | Hardware Avail: Nov-2002 | Software Avail: Jun-2002

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	147	11.0	1	132	12.3
175.vpr	1	257	6.32	1	233	6.98
176.gcc	1	98.8	12.9	1	98.1	13.0
181.mcf	1	244	8.55	1	242	8.64
186.crafty	1	101	11.5	1	101	11.5
197.parser	1	203	10.3	1	197	10.6
252.eon	1	119	12.6	1	102	14.8
253.perlbnk	1	156	13.4	1	156	13.4
254.gap	1	91.4	14.0	1	88.0	14.5
255.vortex	1	130	17.0	1	125	17.6
256.bzip2	1	198	8.78	1	195	8.93
300.twolf	1	374	9.32	1	368	9.45

### Hardware

CPU: Intel Pentium 4 (533 MHz system bus)  
CPU MHz: 2533  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 12K(I) micro-ops + 8KB(D) on chip  
Secondary Cache: 512KB(I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 2 x 256MB PC1066-32 ECC RDRAM  
Disk Subsystem: 1 x 20GB Maxtor 7.2K ATA/100  
Other Hardware:

### Software

Operating System: Windows XP Professional  
Compiler: Intel C++ Compiler 6.0 (020613Z)  
Microsoft Visual Studio .NET (7.0.9466)  
MicroQuill SmartHeap Library 6.01  
File System: NTFS  
System State: Default

## Notes/Tuning Information

### PORTABILITY FLAGS

176.gcc: -Dalloca=\_alloca -F10000000  
186.crafty: -DNT\_i386  
253.perlbnk: -DSPEC\_CPU2000\_NTOS -DPERLDLL -MT  
254.gap: -DSYS\_HAS\_CALLOC\_PROTO -DSYS\_HAS\_MALLOC\_PROTO

### FEEDBACK-DIRECTED OPTIMIZATION

FDO: PASS1= -Qprof\_gen PASS2= -Qprof\_use

### BASE TUNING

C: -Qipo -QxW +FDO shlW32M.lib  
C++: -QxW -GX -GR +FDO

### PEAK TUNING

164.gzip: -Qipo -QxW -O3 +FDO  
175.vpr: -Qipo -QxW -O3 +FDO  
176.gcc: -Qipo -QxW -O3 +FDO  
181.mcf: -Qipo -QxW -O3 +FDO shlW32M.lib  
186.crafty: -Qipo -QxW -O3 +FDO  
197.parser: -Qipo -QxW -O3 +FDO  
252.eon: -Qipo -QxW -O3 +FDO  
253.perlbnk: -Qipo -QxW +FDO shlW32M.lib  
254.gap: -Qipo -QaxW -O3 +FDO



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell  
Precision WorkStation 350 (2.53 GHz P4)

SPECint\_rate2000 = 11.4  
SPECint\_rate\_base2000 = 11.0

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Nov-2002 | Hardware Avail: Nov-2002 | Software Avail: Jun-2002

## Notes/Tuning Information (Continued)

```
255.vortex: -Qwp_ipo -QxW -O3 -Oa +FDO
256.bzip2:  -Qipo -QxW -O3
300.twolf:  -Qipo -QxW -O3 -Oa shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib: MicroQuill SmartHeap Library 6.01
              www.microquill.com
```