



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer pSeries 650 Model 6M2 (1450 MHz, 1 CPU)

SPECint2000 = 935

SPECint_base2000 = 909

SPEC license #: 11 | Tested by: IBM, Austin, TX | Test date: Oct-2002 | Hardware Avail: Dec-2002 | Software Avail: Dec-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	208	673	208	673	
175.vpr	1400	155	902	155	902	
176.gcc	1100	113	974	113	974	
181.mcf	1800	129	1391	124	1452	
186.crafty	1000	124	804	106	941	
197.parser	1800	473	381	482	374	
252.eon	1300	113	1150	113	1150	
253.perlbnk	1800	253	712	227	793	
254.gap	1100	118	936	118	936	
255.vortex	1900	133	1428	133	1434	
256.bzip2	1500	155	965	150	998	
300.twolf	3000	250	1198	247	1216	

Hardware

CPU: POWER4+
CPU MHz: 1450
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip, 1 chip/SCM
CPU(s) orderable: 1,2,3,4 (order by # SCM)
Parallel: No
Primary Cache: 64KBI+32KBD (on chip) per core
Secondary Cache: 1536KB unified (on chip) per chip
L3 Cache: 32MB unified (off-chip) per SCM, 1 SCM in SUT
Other Cache: None
Memory: 8 GB
Disk Subsystem: 1x18.2 GB SCSI
Other Hardware: None

Software

Operating System: AIX 5L V5.2
Compiler: IBM C for AIX, Version 6.0
IBM VisualAge C++ Professional for AIX, Version 6.0
File System: AIX/JFS
System State: Multi-User

Notes/Tuning Information

Integer Portability Flags:

```
gcc:      -ma -DHOST_WORDS_BIG_ENDIAN
crafty:   -DAIX
eon:      -DNEED_EXPLICIT_SPECIALIZATION
          -I. -DNDEBUG
perlbnk: -DSPEC_CPU2000_AIX
gap:      -DSYS_IS_BSD -DSYS_STRING_H -DSYS_HAS_TIME_PROTO
          -DSYS_HAS_MALLOC_PROTO -DSYS_HAS_CALLOC_PROTO
twolf:    -DHAVE_SIGNED_CHAR
```

Base Optimization Flags:

```
C:
-qpdf1/pdf2
-O5 -blpdata -qalign=natural
C++:
-qpdf1/pdf2
-O5 -lhmu -qalign=natural
```

Integer Peak Optimization Flags

164.gzip



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer pSeries 650 Model 6M2 (1450 MHz, 1 CPU)

SPECint2000 = 935

SPECint_base2000 = 909

SPEC license #: 11 | Tested by: IBM, Austin, TX | Test date: Oct-2002 | Hardware Avail: Dec-2002 | Software Avail: Dec-2002

Notes/Tuning Information (Continued)

```

BASEPEAK = 1
"CC      = /usr/vac/bin/xlc"
175.vpr
BASEPEAK = 1
176.gcc
BASEPEAK = 1
181.mcf
fdpr -v -R3
-O5 -blpdata
186.crafty
-qpdf1/pdf2
fdpr -v -R3
-O3 -q64
197.parser
-O5 -blpdata
252.eon
BASEPEAK = 1
253.perlbnk
-qpdf1/pdf2
-O5 -lhmu -qalign=natural
254.gap
BASEPEAK = 1
255.vortex
-qpdf1/pdf2
-O5 -lhmu -qalign=natural
256.bzip2
-qpdf1/pdf2
-O5 -blpdata -qarch=pwr3 -qtune=pwr3
300.twolf
-qpdf1/pdf2
-O5 -lhmu -qalign=natural -blpdata
"CC      = /usr/vac/bin/xlc"

```

SCM: Acronym for "Single-Chip Module"
SUT: Acronym for "System Under Test"

1 processor was deconfigured through the configuration menu.

fpdr: Feedback directed program restructuring tool
/usr/spec2000 filesystem mounted with no JFS log file I/O.
APAR IY 35693 was applied to AIX to enable new hardware support.
ulimits set to unlimited.
C: IBM VAC++ invoked as cc except where noted as xlc
C++: IBM VAC++ invoked as xlc
Large page mode and memory affinity were set as follows:
vmo -r -o lpgg_regions=32 -o lpgg_size=16777216 -o memory_affinity=1
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE \$USER
shutdown -r
export MEMORY_AFFINITY=MCM