



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

## Intel Corporation

Intel D850EMVR motherboard (3.06 GHz, Pentium 4 processor with Hyper-Threading Technology)

SPECint\_rate2000 = 12.8

SPECint\_rate\_base2000 = 12.7

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Oct-2002 | Hardware Avail: Nov-2002 | Software Avail: Apr-2002

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	112	14.4	1	112	14.6
175.vpr	1	207	7.85	1	207	7.84
176.gcc	1	86.7	14.7	1	86.7	14.7
181.mcf	1	235	8.90	1	235	8.89
186.crafty	1	85.4	13.6	1	86.2	13.5
197.parser	1	169	12.4	1	169	12.4
252.eon	1	97.7	15.4	1	89.0	16.9
253.perlbnk	1	130	16.0	1	130	16.0
254.gap	1	75.0	17.0	1	75.0	17.0
255.vortex	1	106	20.9	1	106	20.8
256.bzip2	1	171	10.2	1	171	10.2
300.twolf	1	420	8.28	1	421	8.27

### Hardware

CPU: Intel Pentium 4 Processor with Hyper-Threading Technology(3.06 GHz, 533 MHz bus)  
CPU MHz: 3067  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 12k micro-ops I + 8KBD on chip  
Secondary Cache: 512KB(I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 256 MB (2 128 MB PC1066-32 RDRAM non-ECC modules)  
Disk Subsystem: IBM 120GXP 80 GB IC35L080AVVA07-0 ATA-100  
Other Hardware: None

### Software

Operating System: Windows XP Professional(Build 2600)  
Compiler: Intel C++ Compiler 6.0 Build 020321Z  
Intel Fortran Compiler 6.0 Build 020321Z  
Microsoft Visual C++ 6.0 SP5(for libraries)  
File System: FAT32  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -QxW -Qipo -O3 +FDO
Base tuning for C++ programs: -QxW -Qipo -GX -GR
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -QxW -Qipo -Oa -O3 +FDO
175.vpr: -QxW -Qwp_ipo -O3 +FDO
176.gcc: -QxW -Qipo -O3 +FDO
181.mcf: -QxW -Qipo -O3 +FDO
186.crafty: -QxW -Qipo -Oa -O3 +FDO
197.parser: -QxW -Qipo -O3 +FDO
252.eon: -QxW -Qipo -O3 +FDO
253.perlbnk: -QxW -Qipo -O3 +FDO
254.gap: -QxW -Qipo -O3 +FDO
Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B
Product description located as of 10/2002:
```



# CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**Intel Corporation**

Intel D850EMVR motherboard (3.06 GHz, Pentium 4 processor with Hyper-Threading Technology)

SPECint\_rate2000 = 12.8

SPECint\_rate\_base2000 = 12.7

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Oct-2002 | Hardware Avail: Nov-2002 | Software Avail: Apr-2002

## Notes/Tuning Information (Continued)

<http://developer.intel.com/design/motherbd/mv2/index.htm>

Motherboard ordering information is available at:

<http://program.intel.com/shared/products/boards/d850emv2/index.htm>

The system bus runs at 533 MHz