



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Einix
A4800

SPECfp2000 = 1012

SPECfp_base2000 = 934

SPEC license #: 49 Tested by: AMD Austin TX Test date: Apr-2003 Hardware Avail: Jul-2003 Software Avail: May-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	169	944	152	1050	
171.swim	3100	205	1509	178	1739	
172.mgrid	1800	208	863	206	875	
173.applu	2100	262	802	237	886	
177.mesa	1400	144	974	140	997	
178.galgel	2900	222	1305	175	1654	
179.art	2600	213	1222	200	1300	
183.quake	1300	164	794	133	979	
187.facerec	1900	180	1055	171	1109	
188.amp	2200	247	891	242	909	
189.lucas	2000	163	1230	161	1239	
191.fma3d	2100	230	913	230	913	
200.sixtrack	1100	314	351	288	382	
301.apsi	2600	306	851	286	910	

Hardware

CPU: AMD Opteron 140, 1.4 GHz
 CPU MHz: 1400
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1,2,4
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x512MB PC2700 DDR ECC Reg SDRAM CL2.5
 Disk Subsystem: IDE 7200 RPM
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition
 Compiler: Intel C/C++ 7.0 build 20021212Z and Intel Fortran 7.0 build 20021212Z
 Compaq Visual Fortran Compiler Version 6.6 (Update B)
 Microsoft Visual Studio .NET (libraries)7.0.9466
 MicroQuill Smartheap Library 6.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
 icl and ifl are the Intel C/C++ and Fortran compilers
 f90 is the Compaq Fortran compiler
 shlw32M6.lib is the SmartHeap library V6.0 from MicroQuill www.microquill.com
 Portability:
 178.galgel: -FI -Fe\$@ -link -stack:32000000
 Baseline: C icl +FDO -O3 -QxW -Qipo
 Baseline: Fortran ifl +FDO -O3 -QxW -Qipo
 Peak tuning:
 168.wupwise: ifl +FDO -QxK -Qipo -Ow
 171.swim: f90 -Optimize:5 -alignment:dcommons -alignment:records
 -alignment:sequence -architecture:k7
 -assume:noaccuracy_sensitive -math_library:fast -tune:k7
 172.mgrid: ifl +FDO -O3 -QaxW -Qipo -Oa -Qprefetch-
 173.applu: ifl +FDO -O3 -QxK -Qipo -Qscalar_rep- -Zp8
 177.mesa: icl +FDO -O3 -QxW -Qipo -Oa -Qscalar_rep-
 178.galgel: f90 -Optimize:5 -fast



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Einix
A4800

SPECfp2000 = 1012
SPECfp_base2000 = 934

SPEC license #: 49 | Tested by: AMD Austin TX | Test date: Apr-2003 | Hardware Avail: Jul-2003 | Software Avail: May-2003

Notes/Tuning Information (Continued)

```

179.art:      icl          -Qipo -Oa          -Qunroll14 -Zp4
183.quake:   icl          -O3 -QxK -Qipo -Oa shlw32M6.lib -Zp4
187.facerec: ifl +FD0 -O3 -QaxW -Qipo -Qscalar_rep- -Qunroll11
188.ampp:    icl          -QxW          -Oa
189.lucas:   ifl +FD0 -O3 -QxW -Qipo -Qprefetch-
191.fma3d:   ifl basepeak=1
200.sixtrack: ifl          -Qipo -Oa          -Zp4
301.apsi:    f90 -Optimize:5 -fast
ONESTEP is used for all base and peak runs

```