



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMVR motherboard (2.53 GHz, Pentium 4 processor)

SPECfp2000 = 999

SPECfp_base2000 = 973

SPEC license #: 13 Tested by: Intel Corporation Test date: Jan-2003 Hardware Avail: Oct-2002 Software Avail: Apr-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	130	1234	129	1242	
171.swim	3100	187	1656	181	1709	
172.mgrid	1800	189	952	184	978	
173.applu	2100	212	992	203	1032	
177.mesa	1400	141	995	141	995	
178.galgel	2900	215	1346	205	1413	
179.art	2600	402	647	366	710	
183.quake	1300	110	1182	103	1261	
187.facerec	1900	163	1164	160	1190	
188.ammmp	2200	364	605	364	605	
189.lucas	2000	144	1389	144	1392	
191.fma3d	2100	212	989	211	995	
200.sixtrack	1100	235	468	230	478	
301.apsi	2600	341	761	341	763	

Hardware

CPU: Intel Pentium 4 Processor (2.53 GHz, 533 MHz bus)
CPU MHz: 2533
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 8KBD on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 512 MB (2 256 MB PC1066-32 RDRAM non-ECC modules)
Disk Subsystem: IBM 120GXP 80 GB IC35L080AVVA07-0 ATA-100
Other Hardware: None

Software

Operating System: Windows XP Professional(Build 2600)
Compiler: Intel C++ Compiler 7.0 Build 021018Z
Intel Fortran Compiler 7.0 Build 021028Z
Microsoft Visual Studio .Net 7.0.9466(for libraries)
File System: FAT32
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -Qipo -QxW -O3 +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW -O3 +FDO
171.swim: -Qipo -QxW -O3 +FDO
172.mgrid: -Qipo -QaxW -O3 +FDO
173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO
177.mesa: basepeak=yes
178.galgel: -Qipo -QxW -O3 +FDO
179.art: -Qipo -QxW -O3 -Oa +FDO
183.quake: -Qipo -QxW -Oa -Qrcd +FDO
187.facerec: -Qipo -QxW -O3 +FDO
188.ammmp: basepeak=yes
189.lucas: -Qipo -QxW -O3 +FDO
191.fma3d: -Qipo -QxW -O3 +FDO
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMVR motherboard (2.53 GHz, Pentium 4 processor)

SPECfp2000 = 999

SPECfp_base2000 = 973

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jan-2003 | Hardware Avail: Oct-2002 | Software Avail: Apr-2002

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxW +FDO

301.apsi: -Qipo -QxW -O3 +FDO

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 10/2002:

<http://developer.intel.com/design/motherbd/mv2/index.htm>

Motherboard ordering information is available at:

<http://program.intel.com/shared/products/boards/d850emv2/index.htm>

The system bus runs at 533 MHz