



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMVR motherboard (2.0A GHz, Pentium 4 processor)

SPECfp2000 = 782

SPECfp_base2000 = 766

SPEC license #: 13 Tested by: Intel Corporation Test date: Jan-2003 Hardware Avail: Oct-2002 Software Avail: Apr-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	164	979	162	986	
171.swim	3100	241	1289	234	1327	
172.mgrid	1800	242	744	235	767	
173.applu	2100	269	781	260	806	
177.mesa	1400	178	787	178	787	
178.galgel	2900	269	1079	265	1095	
179.art	2600	516	504	481	540	
183.earthquake	1300	140	929	132	986	
187.facerec	1900	206	922	202	938	
188.ammpp	2200	461	478	461	478	
189.lucas	2000	185	1083	184	1086	
191.fma3d	2100	271	775	270	778	
200.sixtrack	1100	297	370	290	379	
301.apsi	2600	434	600	433	600	

Hardware

CPU: Intel Pentium 4 Processor (2.0A GHz, 400 MHz bus)
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 8KBD on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 512 MB (2 256 MB PC1066-32 RDRAM non-ECC modules)
Disk Subsystem: IBM 120GXP 80 GB IC35L080AVVA07-0 ATA-100
Other Hardware: None

Software

Operating System: Windows XP Professional(Build 2600)
Compiler: Intel C++ Compiler 7.0 Build 021018Z
Intel Fortran Compiler 7.0 Build 021028Z
Microsoft Visual Studio .Net 7.0.9466(for libraries)
File System: FAT32
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -Qipo -QxW -O3 +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW -O3 +FDO
171.swim: -Qipo -QxW -O3 +FDO
172.mgrid: -Qipo -QaxW -O3 +FDO
173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO
177.mesa: basepeak=yes
178.galgel: -Qipo -QxW -O3 +FDO
179.art: -Qipo -QxW -O3 -Oa +FDO
183.earthquake: -Qipo -QxW -Oa -Qrcd +FDO
187.facerec: -Qipo -QxW -O3 +FDO
188.ammpp: basepeak=yes
189.lucas: -Qipo -QxW -O3 +FDO
191.fma3d: -Qipo -QxW -O3 +FDO
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMVR motherboard (2.0A GHz, Pentium 4 processor)

SPECfp2000 = 782

SPECfp_base2000 = 766

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jan-2003 | Hardware Avail: Oct-2002 | Software Avail: Apr-2002

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxW +FDO

301.apsi: -Qipo -QxW -O3 +FDO

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 10/2002:

<http://developer.intel.com/design/motherbd/mv2/index.htm>

Motherboard ordering information is available at:

<http://program.intel.com/shared/products/boards/d850emv2/index.htm>

The system bus runs at 400 MHz