



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Altix 3000 (1000MHz, Itanium 2)

SPECint_rate2000 = 124

SPECint_rate_base2000 = 124

SPEC license #: 4 | Tested by: SGI | Test date: Apr-2003 | Hardware Avail: Feb-2003 | Software Avail: Apr-2003

| Benchmark | Base Copies | Base Runtime | Base Ratio | Copies | Runtime | Ratio |
|-------------|-------------|--------------|------------|--------|---------|-------|
| 164.gzip | 16 | 232 | 112 | 16 | 232 | 112 |
| 175.vpr | 16 | 220 | 118 | 16 | 220 | 118 |
| 176.gcc | 16 | 135 | 152 | 16 | 135 | 152 |
| 181.mcf | 16 | 358 | 93.2 | 16 | 358 | 93.2 |
| 186.crafty | 16 | 144 | 129 | 16 | 144 | 129 |
| 197.parser | 16 | 375 | 89.1 | 16 | 375 | 89.1 |
| 252.eon | 16 | 156 | 154 | 16 | 156 | 154 |
| 253.perlbnk | 16 | 267 | 125 | 16 | 267 | 125 |
| 254.gap | 16 | 207 | 98.6 | 16 | 207 | 98.6 |
| 255.vortex | 16 | 196 | 180 | 16 | 196 | 180 |
| 256.bzip2 | 16 | 233 | 120 | 16 | 233 | 120 |
| 300.twolf | 16 | 382 | 146 | 16 | 382 | 146 |

Hardware

CPU: Intel Itanium 2
CPU MHz: 1000
FPU: Integrated
CPU(s) enabled: 16 cores, 16 chips, 1 core/chip
CPU(s) orderable: 4-64
Parallel: No
Primary Cache: 16KBI + 16KBD (on chip) per CPU
Secondary Cache: 256KB (on chip) per CPU
L3 Cache: 3.0MB (on chip) per CPU
Other Cache: N/A
Memory: 32 GB (16*512MB DIMMS per 4cpu module)
Disk Subsystem: 1 x 36 GB SCSI (Seagate Cheetah 15k rpm)
Other Hardware: None

Software

Operating System: SGI ProPack(TM) v2.1
Compiler: Intel(R) C++ Compiler for Linux 7.1 (Build 20030327)
File System: xfs
System State: Single-user

Notes/Tuning Information

+FDO: PASS1=-prof_gen PASS2=-prof_use

Baseline optimization flags:

C programs: -ipo -O3 +FDO
C++ programs: -ipo -O2 -ansi_alias +FDO

Portability Flags:

176.gcc: -DSPEC_CPU2000_LP64 -Dalloca=_builtin_alloca -D_LIBC
186.crafty: -DLINUX_i386
252.eon: -DSPEC_CPU2000_LP64 -DHAS_ERRLIST
253.perlbnk: -DSPEC_CPU2000_LP64 -DSPEC_CPU2000_NEED_BOOL
-DSPEC_CPU2000_LINUX_IA64 -DSPEC_CPU2000_GLIBC22
254.gap: -DSPEC_CPU2000_LP64 -DSYS_HAS_CALLOC_PROTO -DSYS_IS_USG
-DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
255.vortex: -DSPEC_CPU2000_LP64

Processes were bound to CPUs using dplace.

Peak flags same as baseline (basepeak=true set globally).