



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**SGI**  
SGI Altix 3000 (1300MHz, Itanium 2)

SPECfp\_rate2000 = 142  
SPECfp\_rate\_base2000 = 141

SPEC license #: 4 | Tested by: SGI | Test date: Jun-2003 | Hardware Avail: Jun-2003 | Software Avail: Jun-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	130	114	8	130	114
171.swim	8	138	209	8	138	209
172.mgrid	8	122	137	8	121	138
173.applu	8	74.5	261	8	74.5	261
177.mesa	8	146	89.2	8	146	89.2
178.galgel	8	97.9	275	8	97.9	275
179.art	8	67.8	356	8	67.8	356
183.equake	8	68.1	177	8	68.1	177
187.facerec	8	139	127	8	139	127
188.amp	8	201	102	8	201	102
189.lucas	8	176	106	8	176	106
191.fma3d	8	244	79.7	8	244	79.7
200.sixtrack	8	90.7	113	8	90.7	113
301.apsi	8	317	76.1	8	295	81.7

### Hardware

CPU: Intel Itanium 2  
CPU MHz: 1300  
FPU: Integrated  
CPU(s) enabled: 8 cores, 8 chips, 1 core/chip  
CPU(s) orderable: 4-64  
Parallel: No  
Primary Cache: 16KBI + 16KBD (on chip) per CPU  
Secondary Cache: 256KB (on chip) per CPU  
L3 Cache: 3.0MB (on chip) per CPU  
Other Cache: N/A  
Memory: 16 GB (16\*512MB DIMMS per 4cpu module)  
Disk Subsystem: 1 x 36 GB SCSI (Seagate Cheetah 15k rpm)  
Other Hardware: None

### Software

Operating System: SGI ProPack(TM) v2.2  
Compiler: Intel(R) Fortran Compiler for Linux 7.1 (Build 20030507)  
Intel(R) C++ Compiler for Linux 7.1 (Build 20030507)  
File System: xfs  
System State: Single-user

## Notes/Tuning Information

+FDO: PASS1=-prof\_gen PASS2=-prof\_use

### Baseline optimization flags:

C programs: -ipo -O3 +FDO -ansi\_alias  
Fortran programs: -ipo -O3 +FDO

### Portability Flags:

178.galgel: -FI

### Peak optimization flags:

168.wupwise: basepeak=yes  
171.swim: basepeak=yes  
172.mgrid: -O3 -ipo  
173.applu: basepeak=yes  
177.mesa: basepeak=yes  
178.galgel: basepeak=yes  
179.art: basepeak=yes



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI

SGI Altix 3000 (1300MHz, Itanium 2)

SPECfp\_rate2000 = 142

SPECfp\_rate\_base2000 = 141

SPEC license #: 4 | Tested by: SGI | Test date: Jun-2003 | Hardware Avail: Jun-2003 | Software Avail: Jun-2003

## Notes/Tuning Information (Continued)

183.quake: basepeak=yes  
187.facerec: basepeak=yes  
188.ammmp: basepeak=yes  
189.lucas: -O3 -ipo  
191.fma3d: basepeak=yes  
200.sixtrack: basepeak=yes  
301.apsi: -O3 -ipo

Processes were bound to CPUs using dplace.