



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Altix 3000 (1300MHz, Itanium 2)

SPECint_rate2000 = 601
SPECint_rate_base2000 = 601

SPEC license #: 4 | Tested by: SGI | Test date: Jun-2003 | Hardware Avail: Jun-2003 | Software Avail: Jun-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	64	208	499	64	208	499
175.vpr	64	172	603	64	172	603
176.gcc	64	123	665	64	123	665
181.mcf	64	293	456	64	293	456
186.crafty	64	112	665	64	112	665
197.parser	64	302	442	64	302	442
252.eon	64	123	785	64	123	785
253.perlbnk	64	216	620	64	216	620
254.gap	64	170	482	64	170	482
255.vortex	64	161	879	64	161	879
256.bzip2	64	201	554	64	201	554
300.twolf	64	308	723	64	308	723

Hardware

CPU: Intel Itanium 2
 CPU MHz: 1300
 FPU: Integrated
 CPU(s) enabled: 64 cores, 64 chips, 1 core/chip
 CPU(s) orderable: 4-64
 Parallel: No
 Primary Cache: 16KBI + 16KBD (on chip) per CPU
 Secondary Cache: 256KB (on chip) per CPU
 L3 Cache: 3.0MB (on chip) per CPU
 Other Cache: N/A
 Memory: 64 GB (8*512MB DIMMS per 4cpu module)
 Disk Subsystem: 1 x 36 GB SCSI (Seagate Cheetah 15k rpm)
 Other Hardware: None

Software

Operating System: SGI ProPack(TM) v2.2
 Compiler: Intel(R) C++ Compiler for Linux 7.1 (Build 20030507)
 File System: xfs
 System State: Single-user

Notes/Tuning Information

+FDO: PASS1=-prof_gen PASS2=-prof_use

Baseline optimization flags:

C programs: -ipo -O3 +FDO
 C++ programs: -ipo -O2 +FDO -ansi_alias

Portability Flags:

176.gcc: -DSPEC_CPU2000_LP64 -Dalloca=_builtin_alloca -D_LIBC
 186.crafty: -DLINUX_i386
 252.eon: -DSPEC_CPU2000_LP64 -DHAS_ERRLIST
 253.perlbnk: -DSPEC_CPU2000_LP64 -DSPEC_CPU2000_NEED_BOOL
 -DSPEC_CPU2000_LINUX_IA64 -DSPEC_CPU2000_GLIBC22
 254.gap: -DSPEC_CPU2000_LP64 -DSYS_HAS_CALLOC_PROTO -DSYS_IS_USG
 -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
 255.vortex: -DSPEC_CPU2000_LP64

Processes were bound to CPUs using dplace.

Peak flags same as baseline (basepeak=true set globally).