



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V880 (1050MHz)

SPECfp2000 = 982

SPECfp_base2000 = 845

SPEC license #: 6 Tested by: Sun Microsystems Test date: May-2003 Hardware Avail: May-2003 Software Avail: May-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	203	787	194	823
171.swim	3100	310	999	131	2374
172.mgrid	1800	283	636	283	636
173.applu	2100	326	644	249	842
177.mesa	1400	228	615	217	645
178.galgel	2900	166	1744	139	2088
179.art	2600	29.7	8766	26.8	9703
183.earth	1300	97.3	1337	93.2	1394
187.facerec	1900	179	1060	179	1060
188.amp	2200	422	521	387	569
189.lucas	2000	425	470	325	615
191.fma3d	2100	485	433	438	479
200.sixtrack	1100	307	358	277	397
301.apsi	2600	450	578	451	576

Hardware

CPU: UltraSPARC III Cu
CPU MHz: 1050
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 2,4,8
Parallel: No
Primary Cache: 32KBI+64KBD on chip
Secondary Cache: 8MB(I+D) off chip
L3 Cache: None
Other Cache: None
Memory: 2GB 4-way interleaved
Disk Subsystem: 1 x 36GB
Other Hardware: None

Software

Operating System: Solaris 9 4/03
Compiler: Sun ONE Studio 8
Sun Performance Library 8
File System: ufs with ufs logging
System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC
F90: f90
F77: f90

Floating point base flags:

C: -fast -xipo=2 -xalias_level=std with ONESTEP=yes and feedback
F90: -fast -xipo=2 with ONESTEP=yes and feedback

Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1
171.swim: -fast -xpad=common:3969 -xpagesize=64K -xprefetch=latx:1.6
-Qoption iropt -Atile:skewp,-Ainline:cs=700
(no feedback)



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V880 (1050MHz)

SPECfp2000 = 982
SPECfp_base2000 = 845

SPEC license #: 6 Tested by: Sun Microsystems Test date: May-2003 Hardware Avail: May-2003 Software Avail: May-2003

Notes/Tuning Information (Continued)

```

172.mgrid: -fast -xipo=2
173.applu: -fast -xipo=2
           -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
           -Qoption iropt -Aujam:inner=g
177.mesa: -fast -xipo=2 -xalias_level=strong -xrestrict
           -Wc,-Qms_pipe+unoovf
178.galgel: -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
            RM_SOURCES=lapak.f90
179.art: -fast -xipo=2 -xalias_level=std
          -Wc,-Qms_pipe-prefst,-Qms_pipe+prefolim=11
183.quake: -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec: -fast -xipo=2
188.ampp: -fast -xipo=2 -xalias_level=std -xpagesize=512K -lmopt -lm
189.lucas: -fast -xipo=2 -xprefetch_level=3 -Qoption iropt -Apf:pdl=1
           -Qoption f90comp -array_pad_rows,1977
191.fma3d: -fast -xipo=2 -stackvar -xprefetch_level=3
           -Qoption iropt -Apf:pdl=1
200.sixtrack: -O -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
301.apsi: -fast -xipo=2

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0: rm -rf ./feedback.profile ./SunWS_cache
PASS1: -xprofile=collect:./feedback
PASS2: -xprofile=use:./feedback

```

Portability:

178.galgel: -e -fixed

Shell Environments:

Stack size set to unlimited via "ulimit -s unlimited"

MPSSHEAP=512K

MPSSSTACK=512K

LD_PRELOAD=mpss.so.1

Scheduling class set to Real Time with priority=15 and time quantum=20 via "priocntl -e -c RT -p 15 -t 20"

Kernel Parameters (/etc/system):

set cpu_bringup_set=4

set autoup=900

set tune_t_fsflushr=1

System Settings:

2nd CPU disabled at boot time by using /etc/system parameter "cpu_bringup_set"