



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant DL560 (2.8GHz, Intel Xeon MP)

SPECfp\_rate2000 = 18.2  
SPECfp\_rate\_base2000 = 17.6

SPEC license #: 3 Test id: Hewlett-Packard Company, Houston TX Test date: Sep-2003 Hardware Avail: Jul-2003 Software Avail: Jun-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	146	25.4	2	146	25.3
171.swim	2	590	12.2	2	590	12.2
172.mgrid	2	330	12.7	2	330	12.7
173.applu	2	451	10.8	2	450	10.8
177.mesa	2	128	25.5	2	125	25.9
178.galgel	2	162	41.4	2	164	41.0
179.art	2	290	20.8	2	253	23.8
183.quake	2	210	14.4	2	163	18.5
187.facerec	2	194	22.7	2	189	23.4
188.amp	2	246	20.8	2	245	20.8
189.lucas	2	368	12.6	2	368	12.6
191.fma3d	2	313	15.6	2	313	15.6
200.sixtrack	2	211	12.1	2	208	12.3
301.apsi	2	329	18.3	2	330	18.3

### Hardware

CPU: Intel Xeon MP (2.8GHz, 400MHz bus)  
 CPU MHz: 2800  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading disabled)  
 CPU(s) orderable: 1,2,4  
 Parallel: No  
 Primary Cache: 12K micro-ops I + 8KBD on chip  
 Secondary Cache: 512KB(I+D) on chip  
 L3 Cache: 2048KB(I+D) on chip  
 Other Cache: N/A  
 Memory: 2x1024MB PC2100  
 Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI  
 Other Hardware:

### Software

Operating System: Windows 2000 Advanced Server (Build 2195 SP3)  
 Compiler: Intel C++ Compiler 7.1 Build 20030801Z  
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)  
 Intel Fortran Compiler 7.1 build 20030307Z  
 MicroQuill Smartheap Library 7.0  
 File System: NTFS  
 System State: Hyperthreading disabled in BIOS

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning: -QxW -Qipo -O3 +FDO ONESTEP=yes
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW +FDO ONESTEP=yes
171.swim: -Qipo -QxW -O3 +FDO ONESTEP=yes
172.mgrid: -Qipo -QaxW -O3 +FDO ONESTEP=yes
173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO ONESTEP=yes
177.mesa: -Qipo -QxW -O3 +FDO ONESTEP=yes
178.galgel: -Qipo -QxW -O3 +FDO ONESTEP=yes
179.art: -Qipo -Oa -Qunroll4 -Zp4 ONESTEP=yes
183.quake: -Qipo -QxW -Oa -Qrcd +FDO shlw32M.lib ONESTEP=yes
187.facerec: -Qipo -QaxW -O3 -Qunroll1 -Qscalar_rep- +FDO ONESTEP=yes
188.amp: -QxW -Oa ONESTEP=yes
189.lucas: -Qipo -QaxW
191.fma3d: basepeak=1
```



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant DL560 (2.8GHz, Intel Xeon MP)

SPECfp\_rate2000 = 18.2  
SPECfp\_rate\_base2000 = 17.6

SPEC license #: 3 | Test address: Hewlett-Packard Company, Houston TX | Test date: Sep-2003 | Hardware Avail: Jul-2003 | Software Avail: Jun-2003

## Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxW +FDO ONESTEP=yes  
301.apsi: -Qipo -QxW -O3 +FDO ONESTEP=yes