



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell
PowerEdge 1750 (3.2 GHz Xeon, 1MB L3)

SPECfp_rate2000 = 20.7
SPECfp_rate_base2000 = 20.5

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Oct-2003 | Hardware Avail: Oct-2003 | Software Avail: Apr-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	118	31.5	2	118	31.6
171.swim	2	351	20.5	2	351	20.5
172.mgrid	2	213	19.6	2	213	19.6
173.applu	2	281	17.3	2	288	16.9
177.mesa	2	109	29.9	2	108	30.2
178.galgel	2	211	31.9	2	211	32.0
179.art	2	562	10.7	2	550	11.0
183.quake	2	155	19.5	2	153	19.7
187.facerec	2	155	28.5	2	151	29.2
188.amp	2	312	16.4	2	310	16.5
189.lucas	2	228	20.4	2	226	20.5
191.fma3d	2	232	21.0	2	232	21.0
200.sixtrack	2	191	13.4	2	187	13.6
301.apsi	2	297	20.3	2	295	20.5

Hardware

CPU: Intel Pentium Xeon (533 MHz system bus)
 CPU MHz: 3200
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology disabled)
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 8KB(D) on chip
 Secondary Cache: 512KB(I+D) on chip
 L3 Cache: 1024KB(I+D) on chip
 Other Cache: N/A
 Memory: 4 X 512MB DDR266
 Disk Subsystem: 1 x 17GB Ultra3 Seagate SCSI
 Other Hardware:

Software

Operating System: Windows 2000 Server (SP2)
 Compiler: Intel C++ Compiler 7.1 (20030402Z)
 Intel Fortran Compiler 7.1 (20030402Z)
 Microsoft Visual Studio .NET (7.0.9466)
 File System: NTFS
 System State: Default

Notes/Tuning Information

```

PORTABILITY
  178.galgel: -FI /F32000000
FEEDBACK DIRECTED OPTIMIZATION
  FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
BASE TUNING
  C/F77/F90: -Qipo -QxW -O3 +FDO
PEAK TUNING
  168.wupwise: -Qipo -QxW -O3 +FDO
  171.swim: -Qipo -QxW -O3 +FDO
  172.mgrid: -Qipo -QaxW -O3 +FDO
  173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO
  177.mesa: PASS1= -Qprof_gen PASS2= -Qipo -Qprof_use -QxW -O3 -Oa
  178.galgel: -Qipo -QxW -O3 +FDO
  179.art: -Oa -Qipo -Qunroll4 -Zp4
  183.quake: -QxW -Oa -Qrcd -Qipo +FDO
  187.facerec: -O3 -QaxW -Qipo -Qunroll11 -Qscalar_rep- +FDO
  188.amp: -Oa -QxW

```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell
PowerEdge 1750 (3.2 GHz Xeon, 1MB L3)

SPECfp_rate2000 = 20.7
SPECfp_rate_base2000 = 20.5

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Oct-2003 | Hardware Avail: Oct-2003 | Software Avail: Apr-2003

Notes/Tuning Information (Continued)

189.lucas: -Qipo -QaxW
191.fma3d: basepeak=yes
200.sixtrack: -Qipo -QxW +FDO
301.apsi: -Qipo -QxW -O3 +FDO
ONESTEP=YES is set for all benchmarks
Hyper-Threading Technology disabled in BIOS