



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V480 (1200MHz)

SPECfp2000 = 1084

SPECfp_base2000 = 921

SPEC license #: 6 Tested by: Sun Microsystems Test date: Oct-2003 Hardware Avail: Oct-2003 Software Avail: Dec-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	185	864	176	910
171.swim	3100	314	987	117	2641
172.mgrid	1800	264	683	264	683
173.applu	2100	293	716	224	939
177.mesa	1400	200	698	190	737
178.galgel	2900	149	1947	125	2318
179.art	2600	25.9	10020	23.8	10923
183.earth	1300	90.2	1442	86.9	1497
187.facerec	1900	163	1168	163	1168
188.amp	2200	384	573	356	619
189.lucas	2000	407	491	302	662
191.fma3d	2100	463	454	407	517
200.sixtrack	1100	271	405	243	452
301.apsi	2600	407	639	407	639

Hardware

CPU: UltraSPARC III Cu
CPU MHz: 1200
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 2,4
Parallel: No
Primary Cache: 32KBI+64KBD on chip
Secondary Cache: 8MB(I+D) off chip
L3 Cache: None
Other Cache: None
Memory: 4GB 4-way interleaved
Disk Subsystem: 1 x 18GB SEAGATE ST318304FSUN18G
Other Hardware: None

Software

Operating System: Solaris 9 12/03
Compiler: Sun ONE Studio 8
Sun Performance Library 8
File System: ufs with ufs logging
System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC
F90: f90
F77: f90

Floating point base flags:

C: -fast -xipo=2 -xalias_level=std with ONESTEP=yes and feedback
F90: -fast -xipo=2 with ONESTEP=yes and feedback

Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1
171.swim: -fast -xpad=common:3969 -xpagesize=64K -xprefetch=latx:1.6
-Qoption iropt -Atile:skewp,-Ainline:cs=700
(no feedback)



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V480 (1200MHz)

SPECfp2000 = 1084
SPECfp_base2000 = 921

SPEC license #: 6 Tested by: Sun Microsystems Test date: Oct-2003 Hardware Avail: Oct-2003 Software Avail: Dec-2003

Notes/Tuning Information (Continued)

```

172.mgrid:    basepeak=yes
173.applu:    -fast -xipo=2
              -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
              -Qoption iropt -Aujam:inner=g
177.mesa:     -fast -xipo=2 -xalias_level=strong -xrestrict
              -Wc,-Qms_pipe+unoovf
178.galgel:   -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
              RM_SOURCES=lapak.f90
179.art:      -fast -xipo=2 -xalias_level=std
              -Wc,-Qms_pipe-prefst,-Qms_pipe+prefolim=11
183.quake:   -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec: -fast -xipo=2
188.ampp:    -fast -xipo=2 -xalias_level=std -xpagesize=512K -lmopt -lm
189.lucas:   -fast -xprefetch_level=3 -Qoption iropt -Apf:pdl=1
              -Qoption f90comp -array_pad_rows,1977
191.fma3d:   -fast -xipo=2 -stackvar -xprefetch_level=3
              -Qoption iropt -Apf:pdl=1
200.sixtrack:-O -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
301.apsi:    -fast -xipo=2

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:     -xprofile=collect:./feedback
PASS2:     -xprofile=use:./feedback

```

Portability:

178.galgel: -e -fixed

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=512K
MPSSSTACK=512K
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

set autoup=900
set tune_t_fsflushr=1
set cpu_bringup_set=8

```

System Settings:

```

2nd CPU disabled at boot time by using /etc/system
parameter "cpu_bringup_set"

```