



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP Integrity rx7620 (1300 MHz Itanium 2)

SPECint_rate2000 = 46.0
SPECint_rate_base2000 = 45.3

SPEC license #: 3 Tested by: HP Richardson Test date: Nov-2003 Hardware Avail: Nov-2003 Software Avail: Oct-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	170	38.3	4	170	38.3
175.vpr	4	169	38.5	4	164	39.7
176.gcc	4	92.3	55.3	4	92.3	55.3
181.mcf	4	257	32.5	4	257	32.5
186.crafty	4	95.0	48.8	4	93.2	49.8
197.parser	4	232	35.9	4	232	35.9
252.eon	4	97.3	62.0	4	94.3	63.9
253.perlbnk	4	179	46.6	4	172	48.7
254.gap	4	141	36.1	4	141	36.1
255.vortex	4	127	69.4	4	124	71.1
256.bzip2	4	160	43.5	4	160	43.5
300.twolf	4	270	51.5	4	263	52.9

Hardware

CPU: Intel Itanium 2
 CPU MHz: 1300
 FPU: Integrated
 CPU(s) enabled: 4 cores, 4 chips, 1 core/chip
 CPU(s) orderable: 2,4,6,8
 Parallel: no
 Primary Cache: 16KBI + 16KBD (on chip) per CPU
 Secondary Cache: 256KB (on chip) per CPU
 L3 Cache: 3.0MB (on chip) per CPU
 Other Cache: N/A
 Memory: 8GB (16 * 512MB DIMMs)
 Disk Subsystem: 1x36GB 10K rpm SCSI
 Other Hardware: N/A

Software

Operating System: HPUX11i-TCOE B.11.23
 Compiler: HP C/ANSI C Compiler A.05.52
 HP aC++ Compiler A.05.52
 File System: vxfs
 System State: Multi-user

Notes/Tuning Information

Portability Flags

176.gcc : -DHOST_WORDS_BIG_ENDIAN
 186.crafty : -DHP
 252.eon : -DFMAX_IS_DOUBLE
 253.perlbnk : -DSPEC_CPU2000_HP
 254.gap : -DSPEC_CPU2000_HP -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO
 -DSYS_HAS_TIME_PROTO -DSYS_HAS_CALLOC_PROTO

Base Flags

all : +Oprofile=collect:all/+Oprofile=use
 C : +Ofaster -exec +Odatalayout
 C++ : +Ofaster +inline_level 2 -minshared

Peak Flags

164.gzip : basepeak=true
 175.vpr : +Oprofile=collect:all/+Oprofile=use +Ofaster -exec +Odatalayout
 +Onoptrs_to_globals +Onorecovery
 176.gcc : basepeak=true
 181.mcf : basepeak=true
 186.crafty : +Oprofile=collect:all/+Oprofile=use +Ofaster -exec +Odatalayout



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP Integrity rx7620 (1300 MHz Itanium 2)

SPECint_rate2000 = 46.0
SPECint_rate_base2000 = 45.3

SPEC license #: 3 | Tested by: HP Richardson | Test date: Nov-2003 | Hardware Avail: Nov-2003 | Software Avail: Oct-2003

Notes/Tuning Information (Continued)

```

+Otype_safety=ansi
197.parser : basepeak=true
252.eon : +Oprofile=collect:all/+Oprofile=use +Ofaster +inline_level 2
        -minshared +Otype_safety=ansi
253.perlbnk : +Oprofile=collect:all/+Oprofile=use +Ofaster -exec +Odatalayout
            +Onoptrs_to_globals
            LIBS = /opt/langtools/lib/hpux32/fastmem.o
254.gap : basepeak=true
255.vortex : +Oprofile=collect:all/+Oprofile=use +Ofaster -exec +Odatalayout
            +Onoptrs_to_globals +Onorecovery
256.bzip2 : basepeak=true
300.twolf : +Oprofile=collect:all/+Oprofile=use +Ofaster -exec +Odatalayout
            +Onoptrs_to_globals
            LIBS = /opt/langtools/lib/hpux32/effmem.o

```

Kernel Tunables:

```

dbc_max_pct=20
dbc_min_pct=20
maxdsiz=3221225472
maxssiz=401604608
maxdsiz_64bit=4396972761584
maxssiz_64bit=1073741824
vps_pagesize=4096
vps_ceiling=16384

```

The system under test had the HP-UX 11i v2 (version 11.23) Technical Computing Operating Environment and compilers installed, with the following patches applied:

```

PHSS_29655 aC++ compiler (A.05.52)
PHSS_29656 HP C Compiler (A.05.52)
PHSS_29657 u2comp/be/plugin library Patch
PHSS_29663 Fortran Product Patch, v2.7 to v2.7.2

```

Notes:

System configured as a single partition with 1 cell and 4 processors

Filesystem used for spec runs mounted "tmplog"