



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Altix 3000 (1500MHz, Itanium 2)

SPECint_rate2000 = --
SPECint_rate_base2000 = 114

SPEC license #: 4 | Tested by: SGI | Test date: Jan-2004 | Hardware Avail: Jul-2003 | Software Avail: Dec-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	152	85.3			
175.vpr	8	135	96.3			
176.gcc	8	84.9	120			
181.mcf	8	95.7	174			
186.crafty	8	83.5	111			
197.parser	8	192	87.0			
252.eon	8	85.9	140			
253.perlbnk	8	152	110			
254.gap	8	132	77.4			
255.vortex	8	97.7	180			
256.bzip2	8	129	108			
300.twolf	8	220	126			

Hardware

CPU: Intel Itanium 2
CPU MHz: 1500
FPU: Integrated
CPU(s) enabled: 8 cores, 8 chips, 1 core/chip
CPU(s) orderable: 4-64
Parallel: No
Primary Cache: 16KBI + 16KBD (on chip) per CPU
Secondary Cache: 256KB (on chip) per CPU
L3 Cache: 6.0MB (on chip) per CPU
Other Cache: N/A
Memory: 8 GB (8*512MB PC2700 DIMMS per 4cpu module)
Disk Subsystem: 1 x 36 GB SCSI (Seagate Cheetah 15k rpm)
Other Hardware: None

Software

Operating System: SGI ProPack(TM) v2.3
Compiler: Intel(R) C++ Compiler for Linux 8.0 (Build 20031017)
MicroQuill SmartHeap Library 7.01 (www.microquill.com)
File System: xfs
System State: Single-user

Notes/Tuning Information

+FDO: PASS1=-prof_gen PASS2=-prof_use

Baseline optimization flags:

C programs: -fast -auto_ilp32 +FDO
C++ programs: -fast -ansi_alias +FDO
Extra Libraries: libsmartheap64.a

Portability Flags:

176.gcc: -DSPEC_CPU2000_LP64 -Dalloca=_builtin_alloca -D_LIBC
186.crafty: -DLINUX_i386
252.eon: -DSPEC_CPU2000_LP64 -DHAS_ERRLIST -DFMAX_IS_DOUBLE
253.perlbnk: -DSPEC_CPU2000_LP64 -DSPEC_CPU2000_NEED_BOOL
-DSPEC_CPU2000_LINUX_IA64 -DSPEC_CPU2000_GLIBC22
254.gap: -DSPEC_CPU2000_LP64 -DSYS_HAS_CALLOC_PROTO -DSYS_IS_USG
-DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
255.vortex: -DSPEC_CPU2000_LP64

Processes were bound to CPUs using dplace.