



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V1280 (1200MHz)

SPECfp2000 = 1027

SPECfp_base2000 = 873

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jan-2004 Hardware Avail: Dec-2003 Software Avail: Dec-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	197	813	184	871
171.swim	3100	343	904	135	2295
172.mgrid	1800	260	692	260	692
173.applu	2100	318	660	239	879
177.mesa	1400	203	689	193	725
178.galgel	2900	155	1869	128	2264
179.art	2600	27.7	9373	25.4	10233
183.earth	1300	99.8	1303	97.5	1334
187.facerec	1900	168	1134	168	1134
188.amp	2200	414	532	380	579
189.lucas	2000	435	459	327	611
191.fma3d	2100	486	432	428	490
200.sixtrack	1100	283	388	248	444
301.apsi	2600	429	606	429	606

Hardware

CPU: UltraSPARC III Cu
CPU MHz: 1200
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 4,8,12
Parallel: No
Primary Cache: 32KBI+64KBD on chip
Secondary Cache: 8MB(I+D) off chip
L3 Cache: None
Other Cache: None
Memory: 2GB 4-way interleaved
Disk Subsystem: 1 x 36GB FUJITSU MAN3367M SUN36G
Other Hardware: None

Software

Operating System: Solaris 9 12/03
Compiler: Sun ONE Studio 8
Sun Performance Library 8
File System: ufs with ufs logging
System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC
F90: f90
F77: f90

Floating point base flags:

C: -fast -xipo=2 -xalias_level=std with ONESTEP=yes and feedback
F90: -fast -xipo=2 with ONESTEP=yes and feedback

Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1
171.swim: -fast -xpad=common:3969 -xpagesize=64K -xprefetch=latx:1.6
-Qoption iropt -Atile:skewp,-Ainline:cs=700
(no feedback)



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V1280 (1200MHz)

SPECfp2000 = 1027
SPECfp_base2000 = 873

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jan-2004 Hardware Avail: Dec-2003 Software Avail: Dec-2003

Notes/Tuning Information (Continued)

```

172.mgrid: -fast -xipo=2
173.applu: -fast -xipo=2
           -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
           -Qoption iropt -Aujam:inner=g
177.mesa: -fast -xipo=2 -xalias_level=strong -xrestrict
          -Wc,-Qms_pipe+unoovf
178.galgel: -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
            RM_SOURCES=lapak.f90
179.art: -fast -xipo=2 -xalias_level=std
         -Wc,-Qms_pipe-prefst,-Qms_pipe+prefolim=11
183.quake: -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec: -fast -xipo=2
188.ampp: -fast -xipo=2 -xalias_level=std -xpagesize=512K -lmopt -lm
189.lucas: -fast -xprefetch_level=3 -Qoption iropt -Apf:pdl=1
           -Qoption f90comp -array_pad_rows,1977
191.fma3d: -fast -xipo=2 -stackvar -xprefetch_level=3
           -Qoption iropt -Apf:pdl=1
200.sixtrack: -O -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
301.apsi: -fast -xipo=2

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0: rm -rf ./feedback.profile ./SunWS_cache
PASS1: -xprofile=collect:./feedback
PASS2: -xprofile=use:./feedback

```

Portability:

178.galgel: -e -fixed

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=512K
MPSSSTACK=512K
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

System Settings:

```

Other CPUs disabled at the firmware level using
"disablecomponent" on the System Controller processor
running System Management Services software

```