



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL580 G2 (3.0GHz, Intel Xeon MP)

SPECfp2000 = 1208
SPECfp_base2000 = 1212

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Mar-2004 Hardware Avail: Feb-2004 Software Avail: Mar-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	126	1269	124	1295
171.swim	3100	249	1243	249	1243
172.mgrid	1800	185	973	185	972
173.applu	2100	253	831	245	857
177.mesa	1400	108	1292	108	1293
178.galgel	2900	94.1	3080	96.3	3011
179.art	2600	85.7	3033	91.9	2828
183.quake	1300	133	979	130	1001
187.facerec	1900	147	1296	144	1320
188.amp	2200	164	1343	170	1291
189.lucas	2000	176	1136	176	1138
191.fma3d	2100	236	888	236	888
200.sixtrack	1100	187	589	187	590
301.apsi	2600	276	942	276	942

Hardware

CPU: Intel Xeon MP (3.0GHz, 400MHz bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper Threading Disabled)
CPU(s) orderable: 1,2,4
Parallel: No
Primary Cache: 12K micro-ops I + 8KBD on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: 4096KB(I+D) on chip
Other Cache: N/A
Memory: 16x512MB PC1600
Disk Subsystem: 2x18.2GB 15K Ultra320 SCSI
Other Hardware:

Software

Operating System: Windows 2000 Advanced Server (Build 2195 SP3)
Compiler: Intel C++ Compiler 8.0 Build 20031211Z
Intel Fortran Compiler 8.0 build 20040125Z
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for all programs: -QxN -Qipo -O3 +FDO ONESTEP=yes
Portability flags:
 178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxN +FDO ONESTEP=yes
171.swim: -Qipo -QxN -O3 +FDO ONESTEP=yes
172.mgrid: -Qipo -QaxN -O3 +FDO ONESTEP=yes
173.applu: -Qipo -QxN -O3 -Qscalar_rep- -Qauto +FDO ONESTEP=yes
177.mesa: -Qipo -QxN -O3 +FDO ONESTEP=yes
178.galgel: -Qipo -QxN -O3 +FDO ONESTEP=yes
179.art: -Qipo -Oa -Qunroll4 -Zp4 ONESTEP=yes
183.quake: -Qipo -QxN -Oa -Qrcd +FDO shlw32M.lib ONESTEP=yes
187.facerec: -Qipo -QaxN -O3 -Qunroll11 -Qscalar_rep- +FDO ONESTEP=yes
188.amp: -QxN -Oa ONESTEP=yes
189.lucas: -Qipo -QaxN
191.fma3d: basepeak=1
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL580 G2 (3.0GHz, Intel Xeon MP)

SPECfp2000 =	1208
SPECfp_base2000 =	1212

SPEC license #:	3	Tested by:	Hewlett-Packard Company	Test date:	Mar-2004	Hardware Avail:	Feb-2004	Software Avail:	Mar-2004
-----------------	---	------------	-------------------------	------------	----------	-----------------	----------	-----------------	----------

Notes/Tuning Information (Continued)

```
200.sixtrack: -Qipo -QxN +FDO ONESTEP=yes
301.apsi:      -Qipo -QxN -O3 +FDO ONESTEP=yes
BIOS Configuration Notes
Hyper Threading disabled
```