



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E4900 (8 processor)

SPECfp_rate2000 = 122

SPECfp_rate_base2000 = 102

SPEC license #: 6 Tested by: Sun Microsystems Test date: Mar-2004 Hardware Avail: May-2004 Software Avail: Apr-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	16	287	104	16	266	112
171.swim	16	1103	52.1	16	250	230
172.mgrid	16	671	49.8	16	676	49.4
173.applu	16	411	94.8	16	321	121
177.mesa	16	244	107	16	231	112
178.galgel	16	238	226	16	190	284
179.art	16	58.3	828	16	53.4	903
183.equake	16	205	118	16	202	119
187.facerec	16	207	170	16	206	171
188.amp	16	480	85.0	16	427	95.7
189.lucas	16	661	56.1	16	661	56.1
191.fma3d	16	771	50.5	16	709	55.0
200.sixtrack	16	324	63.1	16	290	70.3
301.apsi	16	568	85.0	16	568	84.9

Hardware

CPU: UltraSPARC s400
CPU MHz: 1050
FPU: Integrated
CPU(s) enabled: 16 cores, 8 chips, 2 cores/chip
CPU(s) orderable: 4, 8, 12 (order by # chips)
Parallel: No
Primary Cache: 32KBI+64KBD per core on chip (64KBI+128KBD on chip)
Secondary Cache: 8MB(I+D) per core off chip (16MB(I+D) off chip)
L3 Cache: None
Other Cache: None
Memory: 32GB 16-way interleaved
Disk Subsystem: Sun StorEdge S1 Disk Array (2x36GB)
Sun StorEdge T3 Array for the Workgroup (9x36GB)
Other Hardware: None

Software

Operating System: Solaris 9 04/04
Compiler: Sun ONE Studio 8
Sun Performance Library 8
File System: ufs with ufs logging
System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC
F90: f90
F77: f90

Floating point base flags:

C: -fast -xipo=2 -xalias_level=std with ONESTEP=yes and feedback
F90: -fast -xipo=2 with ONESTEP=yes and feedback

Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E4900 (8 processor)

SPECfp_rate2000 = 122

SPECfp_rate_base2000 = 102

SPEC license #: 6 Tested by: Sun Microsystems Test date: Mar-2004 Hardware Avail: May-2004 Software Avail: Apr-2004

Notes/Tuning Information (Continued)

```

171.swim:      -fast -xpad=common:3969 -xpagesize=64K -xprefetch=latx:1.6
               -Qoption iropt -Atile:skewp,-Ainline:cs=700
               (no feedback)
172.mgrid:    -fast -xipo=2
173.applu:    -fast -xipo=2
               -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
               -Qoption iropt -Aujam:inner=g
177.mesa:    -fast -xipo=2 -xalias_level=strong -xrestrict
               -Wc,-Qms_pipe+unoovf
178.galgel:  -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
               RM_SOURCES=lapak.f90
179.art:     -fast -xipo=2 -xalias_level=std
               -Wc,-Qms_pipe-prefst,-Qms_pipe+prefolim=11
183.equake:  -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec: -fast -xipo=2
188.ammpp:   -fast -xipo=2 -xalias_level=std -xpagesize=512K -lmopt -lm
189.lucas:   basepeak=yes
191.fma3d:   -fast -xipo=2 -stackvar -xprefetch_level=3
               -Qoption iropt -Apf:pdl=1
200.sixtrack:-O -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
301.apsi:    -fast -xipo=2

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:    rm -rf ./feedback.profile ./SunWS_cache
PASS1:      -xprofile=collect:./feedback
PASS2:      -xprofile=use:./feedback

```

Portability:

178.galgel: -e -fixed

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

Processes were bound to CPUs using submit=pbind

The system was configured with multiple file systems.

The O/S was installed on one disk of the Sun StorEdge S1 Disk Array (ufs, ufs w/logging). The benchmark was run on the Sun StorEdge T3 Array, using H/W Raid 5 and ufs with ufs logging file system.