



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

ION Computer Systems
BX41 (3GHz Xeon MP processor w. 4MB L3 cache)

SPECint2000 = 1486
SPECint_base2000 = 1486

SPEC license #: 2697 Tested by: ION Test date: May-2004 Hardware Avail: May-2004 Software Avail: Apr-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
164.gzip	1400	116	1206	116	1206	[Bar chart showing ratio]			
175.vpr	1400	125	1118	125	1118	[Bar chart showing ratio]			
176.gcc	1100	64.6	1702	64.6	1702	[Bar chart showing ratio]			
181.mcf	1800	106	1701	106	1701	[Bar chart showing ratio]			
186.crafty	1000	82.9	1206	82.9	1206	[Bar chart showing ratio]			
197.parser	1800	138	1306	138	1306	[Bar chart showing ratio]			
252.eon	1300	89.1	1459	89.1	1459	[Bar chart showing ratio]			
253.perlbmk	1800	112	1602	112	1602	[Bar chart showing ratio]			
254.gap	1100	72.8	1511	72.8	1511	[Bar chart showing ratio]			
255.vortex	1900	76.7	2477	76.7	2477	[Bar chart showing ratio]			
256.bzip2	1500	111	1349	111	1349	[Bar chart showing ratio]			
300.twolf	3000	187	1602	187	1603	[Bar chart showing ratio]			

Hardware

CPU: Intel Xeon processor, 400MHz system bus
 CPU MHz: 2985
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip, HyperThreading disabled
 CPU(s) orderable: 1-4
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 8KB(D) on chip
 Secondary Cache: 512KB (I+D) on chip
 L3 Cache: 4096KB (I+D) on chip
 Other Cache: None
 Memory: 2 GB, DDR266, 2.5-3-3, (4x512MB DIMMs)
 Disk Subsystem: 1x 40GB IDE, 5400rpm
 Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux ES release 3
 Compiler: Intel(R) C++ Compiler for Linux 8.0 (Build 20040412Z)
 MicroQuill SmartHeap Library 7.1 (www.microquill.com)
 File System: ext2
 System State: Multi-user, 2.4.21 up kernel

Notes/Tuning Information

Portability Flags:

```
176.gcc: -Dalloca=_alloca -DUSG
186.crafty: -DLINUX_i386
252.eon: -DHAS_ERRLIST
252.eon: srcalt=fmax_errno
253.perlbmk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
           -DSPEC_CPU2000_GLIBC22
254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
         -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
255.vortex: srcalt=closed_files
HyperThreading disabled in BIOS
```

INT Baseline optimization flags:

```
C programs: PASS1= -xN -prof_gen PASS2= -xN -fast -prof_use
C++ programs: PASS1= -xN -prof_gen PASS2= -xN -fast -ansi_alias -prof_use
```

INT Peak optimization flags:

```
164.gzip: basepeak=yes
175.vpr: basepeak=yes
176.gcc: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

ION Computer Systems
BX41 (3GHz Xeon MP processor w. 4MB L3 cache)

SPECint2000 =	1486
SPECint_base2000 =	1486

SPEC license #: 2697 | Tested by: ION | Test date: May-2004 | Hardware Avail: May-2004 | Software Avail: Apr-2004

Notes/Tuning Information (Continued)

```
181.mcf: basepeak=yes
186.crafty: basepeak=yes
197.parser: basepeak=yes
252.eon: basepeak=yes
253.perlbnk: basepeak=yes
254.gap: basepeak=yes
255.vortex: basepeak=yes
256.bzip2: basepeak=yes
300.twolf: PASS1= -xN -prof_gen PASS2= -xN -ipo -Oa -O3 -prof_use
Extra Library: -L${SH_PATH} -lsmartheap (SH_PATH is path to SmartHeap Library)
```