



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D925XCV (AA-400) motherboard (3.6 GHz, Pentium 4 Processor with HT Technology)

SPECint2000 = 1575

SPECint_base2000 = 1510

SPEC license #: 13 Tested by: Intel Corporation Test date: Jun-2004 Hardware Avail: Jul-2004 Software Avail: Dec-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
164.gzip	1400	118	1187	118	1187
175.vpr	1400	135	1041	135	1039
176.gcc	1100	57.2	1922	57.2	1922
181.mcf	1800	136	1325	136	1323
186.crafty	1000	75.2	1331	75.2	1330
197.parser	1800	130	1388	130	1388
252.eon	1300	74.2	1751	62.2	2089
253.perlbnk	1800	106	1696	95.8	1879
254.gap	1100	57.8	1902	57.9	1899
255.vortex	1900	72.2	2632	72.2	2632
256.bzip2	1500	132	1140	128	1172
300.twolf	3000	210	1429	172	1745

Hardware

CPU: Intel Pentium 4 Processor with HT Technology (3.6 GHz, 800 MHz bus)
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip with HT Technology enabled
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 1MB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 1 GB (2x512MB PC2-4300 DDRII 533 CL4-4-4 Micron MT16HTF6464AG-53EB2)
Disk Subsystem: Seagate ST3160023AS 160 GB Serial ATA (7200 RPM, 8MB cache)
Other Hardware: None

Software

Operating System: Windows XP Professional Service Pack 1a
Compiler: Intel C++ Compiler 8.0 Build 20031017Z
Microsoft Visual Studio .Net 7.0(for libraries)
MicroQuill SmartHeap library V6.0
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use (-QxP not used in PASS1)
Base tuning for C programs: -QxP -fast -Qansi_alias +FDO
Base tuning for C++ programs: -QxP -fast -GX -GR
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -QxP -fast -Qansi_alias -Oa +FDO
175.vpr: -QxP -fast -Qansi_alias +FDO
176.gcc: -QxP -fast -Qansi_alias +FDO
181.mcf: -QxP -fast -Qansi_alias +FDO
186.crafty: -QxP -fast -Qansi_alias -Oa +FDO
197.parser: -QxP -fast -Qansi_alias +FDO
252.eon: -QxP -O2 -Qipo +FDO
253.perlbnk: -QxP -fast -Qansi_alias +FDO shlw32M.lib
254.gap: -QxP -fast -Qunroll11 -Zp8 +FDO
255.vortex basepeak=yes
256.bzip2: -fast -Oa -Qunroll11 +FDO
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D925XCV (AA-400) motherboard (3.6 GHz, Pentium 4 Processor with HT Technology)

SPECint2000 = 1575

SPECint_base2000 = 1510

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jun-2004 | Hardware Avail: Jul-2004 | Software Avail: Dec-2003

Notes/Tuning Information (Continued)

300.twolf: -QxP -fast -O3 +FDO shlw32M.lib

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1
Product description located as of 6/2004:

<http://developer.intel.com/design/motherbd/bc/index.htm>

Motherboard is available through Intel OEM Distribution Channel. See

http://www.intel.com/cd/channel/reseller/asm-na/eng/products/box_desktop_boards/intel_boards/p4_boards/p4_dsk_board_d925xvc/index.htm

The system bus runs at 800 MHz

shlw32M.lib is the SmartHeap library V6.0 from <http://www.microquill.com/smartheap/index.html>

An PCIe-16 video card is installed and HT Technology is enabled