



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Supermicro
X6DA8-G2 (3.40 GHz Xeon, 1MB L3 Cache)

SPECfp2000 = 1397
SPECfp_base2000 = 1393

SPEC license #01176 Tested by: Supermicro Inc., San Jose, CA Test date: Jun-2004 Hardware Avail: May-2004 Software Avail: Dec-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	88.7	1803	88.7	1803	
171.swim	3100	142	2181	142	2181	
172.mgrid	1800	141	1281	141	1281	
173.applu	2100	155	1352	150	1397	
177.mesa	1400	94.2	1486	94.2	1486	
178.galgel	2900	132	2194	132	2194	
179.art	2600	270	962	267	975	
183.quake	1300	79.3	1638	79.3	1638	
187.facerec	1900	108	1754	109	1751	
188.amp	2200	233	946	233	946	
189.lucas	2000	106	1890	107	1868	
191.fma3d	2100	159	1322	159	1322	
200.sixtrack	1100	180	610	180	610	
301.apsi	2600	221	1174	221	1174	

Hardware

CPU: Intel Xeon (3.4GHz 800 MHz system bus)
 CPU MHz: 3400
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (HT Technology enabled)
 CPU(s) orderable: 1, 2
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 8KB(D) on chip
 Secondary Cache: 512KB(I+D) on chip
 L3 Cache: 1024KB(I+D) on chip
 Other Cache: N/A
 Memory: 2 x 256MB ECC CL4 PC2 3200 DDRII SDRAM
 Disk Subsystem: 1 x 73GB U320 SCSI, 10K RPM
 Other Hardware:

Software

Operating System: Windows 2003 Enterprise Server
 Compiler: Intel C/C++ Compiler 8.0 (20031229Z)
 Intel Fortran Compiler 8.0 (20031229Z)
 Microsoft Visual Studio .NET (7.0.9466)
 File System: NTFS
 System State: Default

Notes/Tuning Information

PORTABILITY

178.galgel: -FI /F32000000

FEEDBACK DIRECTED OPTIMIZATION

ONESTEP=YES

FDO: PASS1= -Qprof_gen PASS2=-Qprof_use

BASE TUNING

C/F77/F90: -QxN -Qipo -O3 +FDO

PEAK TUNING

168.wupwise: basepeak=yes

171.swim: basepeak=yes

172.mgrid: basepeak=yes

173.applu: -QxN -Qipo -O3 -Qscalar_rep- -Qauto +FDO

177.mesa: -QxN -Qipo -O3 -Oa +FDO

178.galgel: basepeak=yes

179.art: -Qipo -Oa -Qunroll4 -Zp4

183.quake: -QxN -Qipo -O3 -Oa -Qrcd +FDO

187.facerec: -QaxN -Qipo -O3 -Qunroll1 -Qscalar_rep- +FDO



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Supermicro
X6DA8-G2 (3.40 GHz Xeon, 1MB L3 Cache)

SPECfp2000 = 1397

SPECfp_base2000 = 1393

SPEC license #01176 | Tested by: Supermicro Inc., San Jose, CA | Test date: Jun-2004 | Hardware Avail: May-2004 | Software Avail: Dec-2003

Notes/Tuning Information (Continued)

188. ammp: basepeak=yes
189. lucas: -QaxN -Qipo -O3
191. fma3d: basepeak=yes
200. sixtrack: basepeak=yes
301. apsi: basepeak=yes