



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V40z

SPECfp2000 = 1692

SPECfp_base2000 = 1551

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Jul-2004 Hardware Avail: Jul-2004 Software Avail: Jul-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	96.3	1661	76.3	2097	
171.swim	3100	154	2015	145	2131	
172.mgrid	1800	130	1387	110	1630	
173.applu	2100	159	1320	138	1517	
177.mesa	1400	76.7	1826	70.7	1980	
178.galgel	2900	108	2685	98.9	2933	
179.art	2600	170	1532	117	2219	
183.earthquake	1300	96.4	1348	91.1	1427	
187.facerec	1900	85.1	2233	85.1	2233	
188.ammp	2200	160	1371	157	1399	
189.lucas	2000	134	1494	134	1496	
191.fma3d	2100	141	1486	141	1486	
200.sixtrack	1100	148	741	148	741	
301.apsi	2600	175	1486	173	1507	

Hardware

CPU: AMD Opteron (TM) 850
CPU MHz: 2400
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1,2,4
Parallel: No
Primary Cache: 64KBI + 64KBD on chip
Secondary Cache: 1024KB (I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4x1GB, PC2700 CL2.5 DDR SDRAM ECC Registered
Disk Subsystem: SCSI, 73GB, 10K RPM
Other Hardware: None

Software

Operating System: SuSE Linux 8.0 SLES 64 bit (SP3)
Compiler: PathScale EKO Compiler Suite, Release 1.1
SuSE optional gcc 3.3 (from SLES8 SP3)
PGI Fortran 5.2 (build 5.2-0E)
AMD Core Math Library (Version 2.0) for AMD64
File System: Linux/ext3
System State: Multi-user, Run level 3

Notes/Tuning Information

A two-pass compilation method is used where indicated:

+PSFDO indicates PathScale feedback

PASS1: -fb_create fbdata

PASS2: -fb_opt fbdata

+ACML is the AMD Core Math Library V2.0

Compilers:

C: pathcc (PathScale C) unless otherwise noted

Fortran: pathf90 (PathScale f90) unless otherwise noted

If other compilers are used, they are indicated as:

gcc: Gnu C

pgf90: PGI Fortran

Floating Point base tuning:

Fortran: pgf90 -fastsse -Mipa=fast -Msmart

C: pathcc -Ofast -WOPT:mem_opnds=on +PSFDO

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V40z

SPECfp2000 = 1692

SPECfp_base2000 = 1551

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Jul-2004 Hardware Avail: Jul-2004 Software Avail: Jul-2004

Notes/Tuning Information (Continued)

Floating Point peak tuning:

```

168.wupwise: pgf90 -fastsse -Mipa=fast,inline -Msmart
171.swim: -Ofast -OPT:ro=3 -LNO:fusion=2:prefetch=2
172.mgrid: -O3 -OPT:Ofast
           -LNO:fusion=2:blocking=off:ou_max=5:sclrze=off:prefetch=2
           -OPT:unroll_times=8:unroll_size=256:ro=3
           -CG:gcm=off:cflow=off
173.applu: -O3 -ipa
           -LNO:fusion=2:interchange=OFF:blocking=OFF:ou_prod_max=10
           :ou_max=5:prefetch=2 -OPT:IEEE_arith=1:ro=3:unroll_size=0
           -TENV:X=4 -WOPT:mem_opnds=on:retype_expr=on:val=0 -CG:local_fwd_sched=on
177.mesa: -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +PSFDO
178.galgel: pgf90 -fastsse -Mipa=fast -mp +ACML
           RM_SOURCES=lapak.f90 ONESTEP
179.art: -O3 -OPT:Ofast -fno-math-errno -m32 +PSFDO
183.earthquake: gcc -DSPEC_CPU2000_LP64 -O3 -funroll-all-loops -ffast-math
           -finline-limit=2000 ONESTEP
187.facerec: basepeak=true
188.ammp: -O3 -OPT:alias=disjoint:unroll_times=8:Ofast:ro=3
           -fno-math-errno -TENV:X=4 +PSFDO
189.lucas: pgf90 -fastsse -Mipa=fast,inline -Msmart
191.fma3d: basepeak=true
200.sixtrack: basepeak=true
301.apsi: -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0:blocking=off
           -IPA:linear=on:plimit=525

```

Portability:

178.galgel: -Mfixed

Notes:

BIOS build 2.1.0.9E, default setting was used.
Only one CPU was present in the system, other CPUs were physically removed.