



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML370 G4 (3.6GHz, Intel Xeon)

SPECfp2000 = 1523
SPECfp_base2000 = 1504

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jul-2004 Hardware Avail: Nov-2004 Software Avail: Aug-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	67.8	2358	67.8	2359	
171.swim	3100	138	2244	138	2244	
172.mgrid	1800	133	1357	133	1356	
173.applu	2100	147	1430	142	1478	
177.mesa	1400	88.7	1579	89.0	1573	
178.galgel	2900	126	2302	126	2304	
179.art	2600	216	1204	222	1173	
183.quake	1300	75.7	1718	62.6	2075	
187.facerec	1900	106	1798	107	1784	
188.amp	2200	218	1010	218	1010	
189.lucas	2000	98.7	2027	100	1997	
191.fma3d	2100	145	1445	145	1445	
200.sixtrack	1100	171	645	171	644	
301.apsi	2600	226	1148	226	1149	

Hardware

CPU: Intel Xeon (3.6GHz, 1MB L2, 800MHz bus)
CPU MHz: 3600
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (HT Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 16K micro-ops I + 16KBD on chip
Secondary Cache: 1024KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8x512MB DDR2-400
Disk Subsystem: 1x18.2GB 15K Ultra320 SCSI
Other Hardware:

Software

Operating System: Windows Server 2003 Standard (Build 3790)
Compiler: Intel C++ Compiler 8.0 Build 20031211Z
Intel Fortran Compiler 8.0 build 20040125Z
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
+FDO*: FDO (-QxP not used in PASS1 to enable cross-compilation)

Base tuning Base tuning: -QxP -fast -Qansi_alias +FDO*

Portability flags:

178.galgel: -FI /F32000000

Peak tuning:

168.wupwise: -QxP -fast -Qansi_alias +FDO*
171.swim: -QxP -fast -f77rtl +FDO ONESTEP=yes
172.mgrid: -QxP -fast -Qansi_alias +FDO*
173.applu: -QxP -fast -Qscalar_rep- -Qauto -f77rtl +FDO ONESTEP=yes
177.mesa: -QxP -fast +FDO ONESTEP=yes
178.galgel: -QxP -fast +FDO ONESTEP=yes
179.art: -fast -Oa -Qunroll4 -Zp4 ONESTEP=yes
183.quake: -QxP -fast -Oa -Qrcd +FDO ONESTEP=yes shlw32M.lib
187.facerec: -QaxN -fast -Qunroll1 -Qscalar_rep- -fpp +FDO ONESTEP=yes



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant ML370 G4 (3.6GHz, Intel Xeon)

SPECfp2000 = 1523
SPECfp_base2000 = 1504

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jul-2004 | Hardware Avail: Nov-2004 | Software Avail: Aug-2004

Notes/Tuning Information (Continued)

```
188. ammp:      basepeak=1
189. lucas:     -QaxN -fast
191. fma3d:     basepeak=1
200. sixtrack: -QxP  -fast
301. psi:       -QxP  -fast
                +FDO*
                -f77rtl +FDO ONESTEP=yes
BIOS Configuration Notes
HT Technology disabled
```