



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V440 (1600MHz)

SPECint_rate2000 = 38.7
SPECint_rate_base2000 = 33.6

SPEC license #: 6 Tested by: Sun Microsystems Test date: Nov-2004 Hardware Avail: Nov-2004 Software Avail: Jan-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	200	32.5	4	179	36.3
175.vpr	4	220	29.5	4	214	30.4
176.gcc	4	189	27.0	4	117	43.5
181.mcf	4	488	17.1	4	311	26.9
186.crafty	4	115	40.5	4	95.8	48.4
197.parser	4	276	30.3	4	245	34.1
252.eon	4	126	47.8	4	126	47.8
253.perlbnk	4	230	36.3	4	207	40.4
254.gap	4	171	29.8	4	156	32.7
255.vortex	4	139	63.5	4	130	67.6
256.bzip2	4	226	30.7	4	223	31.1
300.twolf	4	375	37.2	4	356	39.1

Hardware

CPU: UltraSPARC IIIi
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 4 cores, 4 chips, 1 core/chip
CPU(s) orderable: 2,4
Parallel: No
Primary Cache: 32KBI+64KBD on chip
Secondary Cache: 1MB(I+D) on chip
L3 Cache: None
Other Cache: None
Memory: 16GB
Disk Subsystem: 1 x 73GB
Other Hardware: None

Software

Operating System: Solaris 10
Compiler: Sun Studio 9
File System: ufs
System State: Multi-User

Notes/Tuning Information

Compiler invocation:
C: cc
CXX: CC

Integer base flags:
-fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:
ONESTEP=yes and feedback for all benchmarks

164.gzip: -xO5 -xbuiltin=%all -xtarget=native -xalias_level=std
-xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100
175.vpr: -fast -xalias_level=std -xipo=2
-Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=100,
-Qeps:do_spec_load=1 -lmopt -lm
176.gcc: -fast -xipo=2 -l12amm
181.mcf: -fast -xipo=2 -xprefetch_level=3 -Wc,-Qeps:enabled=1
-W2,-Apf:l1list=3:noinnerl1list



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V440 (1600MHz)

SPECint_rate2000 = 38.7
SPECint_rate_base2000 = 33.6

SPEC license #: 6 | Tested by: Sun Microsystems | Test date: Nov-2004 | Hardware Avail: Nov-2004 | Software Avail: Jan-2005

Notes/Tuning Information (Continued)

```

186.crafty: -fast -xinline= -xipo=2 -xalias_level=strong -W2,-Ashort_ldst
            Feedback adds -xlinkopt in PASS2
197.parser: -fast -xipo=2 -xalias_level=strong
            -Wc,-Qgsched-T6,-Qipa:valueprediction
252.eon:    basepeak = yes
253.perlbnk: -xO5 -xtarget=native -xmemalign=4s -xipo
            -Wc,-Qeps:enabled=1,-Qeps:ws=8 -xalias_level=std
            -xsafe=mem -Wc,-Qiselect-funcalign=32,-Qicache-chbab=1 -Wc,
            -Qiselect-sw_pf_tbl_th=20,-Qeps:do_spec_load=1 -xprefetch=no
254.gap:    -fast -xipo=2 -xalias_level=strong -xvector
            -xprefetch_level=3 -W2,-Abcopy
255.vortex: -fast -xrestrict -xipo=2
            -W2,-crit,-Ainline:recursion=1:cs=500:irs=6000
            -Wc,-Qeps:enabled=1,-Qdepgraph-early_cross_call=1,
            -Qiselect-funcalign=32,-Qpeep-Sh0 -ll2amm
256.bzip2:  -fast -xipo=2 -xalias_level=strong -xrestrict
            -Wc,-Qeps:enabled=1
300.twolf:  -fast -xalias_level=strong -xsafe=mem -xipo=2
            -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:     -xprofile=collect:./feedback
PASS2:     -xprofile=use:./feedback

```

Portability:

```

176.gcc:   -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon:   -library=iostream
            srcalt=fmax_errno
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap:   -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
            -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=512K
MPSSSTACK=512K
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```