



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

ION Computer Systems
LN10J (3.4GHz Xeon processor w. 1MB L2 cache)

SPECint_rate2000 = 27.1
SPECint_rate_base2000 = 27.1

SPEC license #: 2697 | Tested by: ION | Test date: Jan-2005 | Hardware Avail: Dec-2004 | Software Avail: Dec-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	2	123	26.4	2	123	26.4
175.vpr	2	193	16.8	2	193	16.8
176.gcc	2	81.2	31.4	2	81.2	31.4
181.mcf	2	441	9.48	2	441	9.48
186.crafty	2	67.2	34.5	2	67.2	34.5
197.parser	2	195	21.4	2	195	21.4
252.eon	2	61.6	48.9	2	61.6	48.9
253.perlbnk	2	94.6	44.1	2	94.6	44.1
254.gap	2	74.9	34.1	2	74.9	34.1
255.vortex	2	87.3	50.5	2	87.3	50.5
256.bzip2	2	157	22.1	2	157	22.1
300.twolf	2	356	19.5	2	356	19.5

Hardware

CPU: Intel Xeon processor, 800MHz system bus
 CPU MHz: 3392
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip, HyperThreading disabled
 CPU(s) orderable: 1-2
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 8KB(D) on chip
 Secondary Cache: 1MB (I+D) on chip
 L3 Cache: None
 Other Cache: None
 Memory: 4GB (4x1GB DDR2-400 DIMMs)
 Disk Subsystem: 80GB Seagate SATA disk
 Other Hardware: None

Software

Operating System: SuSE Linux Professional 9.1 for EM64T, 2.6.4-52-smp x86_64
 Compiler: Intel(R) C Compiler for EM64T, V8.1 (Build 20041123)
 Intel(R) C++ Compiler for EM64T, V8.1 (Build 20041123)
 File System: ext3
 System State: Multi-user, run level 3

Notes/Tuning Information

Portability Flags:

```
176.gcc: srcalt=64bitgcc35
186.crafty: -DLINUX_i386
252.eon: -DHAS_ERRLIST
252.eon: srcalt=stdcpp
253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
           -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
         -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
         -DSPEC_CPU2000_LP64
255.vortex: -DSPEC_CPU2000_LP64
255.vortex: srcalt=closed_files
```

HyperThreading disabled in BIOS

INT Baseline optimization flags:

```
C programs: -xP -fast +FDO
C++ programs: -xP -fast +FDO
```

INT Peak optimization flags:



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

ION Computer Systems
LN10J (3.4GHz Xeon processor w. 1MB L2 cache)

SPECint_rate2000 = 27.1
SPECint_rate_base2000 = 27.1

SPEC license #: 2697 | Tested by: ION | Test date: Jan-2005 | Hardware Avail: Dec-2004 | Software Avail: Dec-2004

Notes/Tuning Information (Continued)

164.gzip: basepeak=yes
175.vpr: basepeak=yes
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: basepeak=yes
197.parser: basepeak=yes
252.eon: basepeak=yes
253.perlbnk: basepeak=yes
254.gap: basepeak=yes
255.vortex: basepeak=yes
256.bzip2: basepeak=yes
300.twolf: basepeak=yes