



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL25p (AMD Opteron (TM) 252)

SPECint2000 = 1764
SPECint_base2000 = 1582

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jan-2005 Hardware Avail: Feb-2005 Software Avail: Jan-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	88.6	1580	89.1	1572	
175.vpr	1400	111	1258	108	1291	
176.gcc	1100	62.5	1761	62.5	1761	
181.mcf	1800	236	763	150	1197	
186.crafty	1000	44.1	2268	44.2	2265	
197.parser	1800	151	1192	124	1453	
252.eon	1300	57.6	2257	48.5	2683	
253.perlbmk	1800	102	1770	94.2	1911	
254.gap	1100	67.2	1637	64.4	1708	
255.vortex	1900	74.2	2561	68.6	2771	
256.bzip2	1500	103	1450	103	1450	
300.twolf	3000	214	1399	163	1835	

Hardware

CPU: AMD Opteron (TM) 252
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x2048MB PC3200 DDR 400
 Disk Subsystem: 2x18.2GB SCSI
 Other Hardware:

Software

Operating System: SuSE Linux Enterprise Server 9 for AMD64
 SuSE kernel 2.6.5-7.97-smp
 Compiler: PathScale EKO Compiler Suite, Release 1.4
 File System: Linux/ext3
 System State: Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
Base tuning for C programs: -O3 -ipa +FDO
Base tuning for C++ programs: -Ofast +FDO
Portability flags:
 186.crafty: -DLINUX_i386
 252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64 srcalt=fmax_errno
 253.perlbmk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
             -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
 254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
          -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
          -DSPEC_CPU2000_LP64
 255.vortex: -DSPEC_CPU2000_LP64 srcalt=closed_files
 300.twolf: -DHAVE_SIGNED_CHAR
Peak tuning:
 164.gzip: -Ofast +FDO
 175.vpr: -O2 -ipa -OPT:alias=disjoint -CG:p2align_freq=500000 +FDO
 loader: -INLINE:aggressive=on
          -IPA:space=300:plimit=10000:callee_limit=5000:linear=on
 176.gcc: basepeak=true
 181.mcf: -O3 -ipa -IPA:field_reorder=on -m32 +FDO
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL25p (AMD Opteron (TM) 252)

SPECint2000 = 1764
SPECint_base2000 = 1582

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jan-2005 Hardware Avail: Feb-2005 Software Avail: Jan-2005

Notes/Tuning Information (Continued)

```
186.crafty: -Ofast +FDO
197.parser: -O3 -ipa -m32 +FDO
  loader:   -IPA:ctype=on
252.eon:    -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -OPT:treeheight=on
          -TENV:X=4:frame_pointer=off -fno-exceptions -LNO:fu=10:full_unroll_outer=on
          +FDO
  loader:   -IPA:plimit=4000:pu_reorder=1
253.perlbnk: -O3 -ipa +FDO
  loader:   -IPA:plimit=10000
254.gap:    -O3 -ipa -OPT:transform_to_memlib=on
255.vortex: -Ofast -IPA:space=70:plimit=3000
          -OPT:goto=off:unroll_analysis=off:unroll_size=0:unroll_times_max=8
          -LNO:opt=0 -TENV:X=4 +FDO
256.bzip2:  basepeak=true
300.twolf:  -O2 -OPT:unroll_times_max=8:unroll_size=256:alias=disjoint:Ofast
          -CG:gcm=off:p2align_freq=100000 -WOPT:mem_opnds=on -m32 +FDO
```

BIOS Configuration Notes
Node Interleaving Disabled