



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V40z

SPECfp_rate2000 = 87.1
SPECfp_rate_base2000 = 79.6

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Feb-2005 Hardware Avail: Apr-2005 Software Avail: Jan-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	70.9	105	4	59.7	124
171.swim	4	131	110	4	126	114
172.mgrid	4	114	73.0	4	103	81.2
173.applu	4	131	74.2	4	113	86.5
177.mesa	4	71.4	91.0	4	65.9	98.6
178.galgel	4	104	129	4	94.9	142
179.art	4	133	90.5	4	87.8	137
183.quake	4	97.3	62.0	4	90.2	66.9
187.facerec	4	98.1	89.9	4	96.8	91.0
188.amp	4	159	64.2	4	150	68.3
189.lucas	4	104	89.3	4	104	89.0
191.fma3d	4	142	68.7	4	141	68.9
200.sixtrack	4	134	38.1	4	131	38.8
301.apsi	4	164	73.5	4	159	75.9

Hardware

CPU: AMD Opteron (TM) 852
CPU MHz: 2600
FPU: Integrated
CPU(s) enabled: 4 cores, 4 chips, 1 core/chip
CPU(s) orderable: 1,2,4
Parallel: No
Primary Cache: 64KBI + 64KBD on chip
Secondary Cache: 1024KB (I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 16GB (8x2GB, PC3200 CL3 DDR)
Disk Subsystem: SCSI, 73GB, 10K RPM
Other Hardware: None

Software

Operating System: SUSE LINUX Enterprise Server 9
Compiler: PathScale EKOPath Compiler Suite, Release 2.0
AMD Core Math Library V2.5.1
File System: Linux/ext3
System State: Multi-user, Run level 3

Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
+ACML -L/opt/acml2.5.1/pathscale64/lib -lacml,
      means linking with AMD Core Math Library V2.5.1
```

Baseline optimization

```
C programs: -Ofast -WOPT:mem_opnds=on +FDO
Fortran programs: -Ofast -LNO:fusion=2 -OPT:fast_complex +FDO
```

Portability Flags:

```
178.galgel: -fixedform
```

Peak Tuning:

```
168.wupwise : -Ofast -LNO:prefetch Ahead=5:prefetch=3
              -OPT:unroll_times_max=8:unroll_size=128:IEEE NaN_Inf=off:ro=3 -TENV:X=4
              -IPA:space=1000:linear=on:plimit=50000:callee_limit=5000
              -INLINE:aggressive=on
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V40z

SPECfp_rate2000 = 87.1
SPECfp_rate_base2000 = 79.6

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Feb-2005 Hardware Avail: Apr-2005 Software Avail: Jan-2005

Notes/Tuning Information (Continued)

```

171.swim      : -Ofast -LNO:fusion=2 -m3dnow
172.mgrid     : -O3 -LNO:fusion=2:blocking=off
               -OPT:Ofast:unroll_times_max=8:unroll_size=256:ro=3
               -CG:gcm=off:cflow=off -m3dnow
173.applu     : -Ofast -CG:local_fwd_sched=on
               -LNO:fusion=2:fission=2:full_unroll_size=10000:prefetch=3
               -OPT:ro=3 -TENV:X=3 -WOPT:val=2
177.mesa      : -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +FDO
178.galgel    : -Ofast -OPT:fast_complex -CG:use_movlpd=on +FDO +ACML
               RM_SOURCES=lapak.f90
179.art       : -O3 -OPT:ro=2:div_split=on:alias=typed -fno-math-errno -m32
183.earth     : -Ofast -WOPT:mem_opnds=on -m32
187.facerec   : -Ofast -OPT:treeheight=on:IEEE_NaN_Inf=off:ro=3 -CG:load_exe=0
               -LNO:fusion=2 -IPA:plimit=1500 +FDO
188.ammp      : -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
               -fno-math-errno -TENV:X=4 +FDO
189.lucas     : -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 +FDO
191.fma3d     : -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
               -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack  : -O3 -OPT:Ofast:Olimit=6000 -fno-math-errno -CG:load_exe=1 +FDO
301.apsi      : -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0

```

Default BIOS setting was used.