



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## IBM

AMD Opteron LS20 for IBM eServer Blade Center (AMD Opteron (TM) 252)

SPECfp2000 = 2016

SPECfp\_base2000 = 1855

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Apr-2005 | Hardware Avail: Apr-2005 | Software Avail: Jan-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
168.wupwise	1600	65.3	2451	56.6	2825	[Bar chart showing ratio 2825]			
171.swim	3100	125	2489	120	2585	[Bar chart showing ratio 2585]			
172.mgrid	1800	108	1670	95.6	1882	[Bar chart showing ratio 1882]			
173.applu	2100	121	1731	104	2019	[Bar chart showing ratio 2019]			
177.mesa	1400	70.4	1989	64.5	2170	[Bar chart showing ratio 2170]			
178.galgel	2900	97.2	2983	98.2	2952	[Bar chart showing ratio 2952]			
179.art	2600	110	2356	74.0	3513	[Bar chart showing ratio 3513]			
183.earth	1300	80.2	1622	75.5	1722	[Bar chart showing ratio 1722]			
187.facerec	1900	88.3	2151	85.1	2233	[Bar chart showing ratio 2233]			
188.ammmp	2200	150	1465	139	1577	[Bar chart showing ratio 1577]			
189.lucas	2000	97.2	2059	97.2	2058	[Bar chart showing ratio 2058]			
191.fma3d	2100	130	1614	130	1615	[Bar chart showing ratio 1615]			
200.sixtrack	1100	132	836	129	850	[Bar chart showing ratio 850]			
301.apsi	2600	159	1638	152	1709	[Bar chart showing ratio 1709]			

### Hardware

CPU: AMD Opteron 252  
CPU MHz: 2600  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 64KBI + 64KBD on chip  
Secondary Cache: 1024KB (I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 4x2048MB, DDR400  
Disk Subsystem: SCSI, 36GB 10K RPM  
Other Hardware: None

### Software

Operating System: SuSE Linux 9.0 SLES 64 bit Kernel 2.6.5-7.139-smp (SP1)  
Compiler: PathScale EKO Compiler Suite, Release 2.0  
File System: Linux/reiserfs  
System State: Multi-user, run level 3

## Notes/Tuning Information

Tested by IBM Corporation

+FDO: PASS1= -fb\_create fbdata PASS2= -fb\_opt fbdata

Baseline optimization

C: pathcc -Ofast -WOPT:mem\_opnds=on +FDO  
Fortran: pathf90 -Ofast -LNO:fusion=2

Portability Flags:

178.galgel: -fixedform

Peak Tuning:

168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3  
-OPT:unroll\_times\_max=8:unroll\_size=128:IEEE\_NaN\_Inf=off:ro=3 -TENV:X=4  
-IPA:space=1000:linear=on:plimit=50000:callee\_limit=5000  
-INLINE:aggressive=on

171.swim: -Ofast -LNO:fusion=2 -m3dnow

172.mgrid: -O3 -LNO:fusion=2:blocking=off



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## IBM

AMD Opteron LS20 for IBM eServer Blade Center (AMD Opteron (TM) 252)

SPECfp2000 = 2016

SPECfp\_base2000 = 1855

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Apr-2005 | Hardware Avail: Apr-2005 | Software Avail: Jan-2005

### Notes/Tuning Information (Continued)

```

- OPT:Ofast:unroll_times_max=8:unroll_size=256:ro=3
- CG:gcm=off:cflow=off -m3dnow
173.applu: -Ofast -CG:local_fwd_sched=on
- LNO:fusion=2:fission=2:full_unroll_size=10000:prefetch=3
- OPT:ro=3 -TENV:X=3 -WOPT:val=2
177.mesa: -O2 -ipa -OPT:Ofast -fno-math-errno
- CG:local_fwd_sched=on +FDO
178.galgel: -Ofast -OPT:fast_complex
- CG:use_movlpd=on +FDO
179.art: -O3 -OPT:ro=2:div_split=on:alias=typed
- fno-math-errno -m32
183.equake: -Ofast -WOPT:mem_opnds=on -m32
187.facerec: -Ofast -OPT:treeheight=on:IEEE_NaN_Inf=off:ro=3
- CG:load_exe=0 -LNO:fusion=2 -IPA:plimit=1500 +FDO
188.ammp: -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
- fno-math-errno -TENV:X=4 +FDO
189.lucas: -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 +FDO
191.fma3d: -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
- WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:Olimit=6000 -fno-math-errno
- CG:load_exe=1 +FDO
301.apsi: -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0

```