



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation  
IBM eServer xSeries 236 (3.4 GHz Intel Xeon)

SPECfp\_rate2000 = 20.2  
SPECfp\_rate\_base2000 = 19.9

SPEC license #: 11 | Tested by: IBM, Research Trinagle Park, NC | Test date: Jun-2005 | Hardware Avail: Feb-2005 | Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	64.2	28.9	1	64.2	28.9
171.swim	1	137	26.3	1	137	26.3
172.mgrid	1	124	16.9	1	124	16.9
173.applu	1	147	16.6	1	148	16.5
177.mesa	1	94.0	17.3	1	94.0	17.3
178.galgel	1	86.4	39.0	1	86.4	39.0
179.art	1	67.0	45.0	1	67.0	45.0
183.quake	1	68.8	21.9	1	57.1	26.4
187.facerec	1	108	20.4	1	108	20.4
188.amp	1	185	13.8	1	185	13.8
189.lucas	1	99.8	23.2	1	98.9	23.5
191.fma3d	1	150	16.3	1	150	16.3
200.sixtrack	1	179	7.12	1	177	7.22
301.apsi	1	208	14.5	1	208	14.5

### Hardware

CPU: Intel Xeon (3.4 GHz Xeon, 2MB L2 Cache, 800 MHz system bus)  
CPU MHz: 3400  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 12K(I) micro-ops + 16KB(D) on chip  
Secondary Cache: 2048KB(I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8 x 512 MB ECC PC2-3200 Single Rank  
Disk Subsystem: 73GB SCSI 10K RPM  
Other Hardware:

### Software

Operating System: Windows Server 2003 Standard Edition  
Compiler: Intel C/C++ Compiler 8.1 (20050409)  
Intel Fortran Compiler 8.1 (20050405Z)  
Microsoft Visual Studio .NET 13.0.9466 (for libraries)  
MicroQuill Smartheap Library 7.30  
File System: NTFS  
System State: Default

## Notes/Tuning Information

### GENERAL

ONESTEP=yes  
+FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

### PORTABILITY

178.galgel: -FI /F32000000

### BASE TUNING

C/F77/F90: -fast -QxP -Qansi\_alias +FDO

### PEAK TUNING

168.wupwise: basepeak=yes  
171.swim: -fast -QxP -f77rtl +FDO  
172.mgrid: basepeak=yes  
173.applu: -fast -QxP -Qscalar\_rep- -Qauto -f77rtl +FDO  
177.mesa: basepeak=yes  
178.galgel: basepeak=yes  
179.art: basepeak=yes  
183.quake: -fast -QxP -Oa -Qrcd +FDO shlW32M.lib  
187.facerec: basepeak=yes



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries 236 (3.4 GHz Intel Xeon)

SPECfp\_rate2000 = 20.2

SPECfp\_rate\_base2000 = 19.9

SPEC license #: 11 | Tested by: IBM, Research Triangle Park, NC | Test date: Jun-2005 | Hardware Avail: Feb-2005 | Software Avail: Apr-2005

## Notes/Tuning Information (Continued)

188. ammp: basepeak=yes  
189. lucas: -fast -QxP  
191. fma3d: basepeak=yes  
200. sixtrack: -QxP -Qipo +FDO  
301. apsi: -fast -QxP -f77rtl +FDO