



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY TX200 S2, 64-bit Intel Xeon 3.40 GHz

SPECfp2000 = 1668
SPECfp_base2000 = 1668

SPEC license #: 22 Tested by: Fujitsu Siemens Computers Test date: May-2005 Hardware Avail: Mar-2005 Software Avail: Mar-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	67.7	2363	67.7	2363	
171.swim	3100	148	2096	148	2096	
172.mgrid	1800	128	1411	128	1411	
173.applu	2100	151	1395	151	1395	
177.mesa	1400	95.4	1468	95.4	1468	
178.galgel	2900	87.6	3310	87.6	3310	
179.art	2600	68.5	3794	68.5	3794	
183.earthquake	1300	59.6	2183	59.6	2183	
187.facerec	1900	113	1680	113	1680	
188.ammpp	2200	217	1016	217	1016	
189.lucas	2000	105	1910	105	1910	
191.fma3d	2100	156	1342	156	1342	
200.sixtrack	1100	179	614	179	614	
301.apsi	2600	213	1223	213	1223	

Hardware

CPU: 64-bit Intel Xeon (3.40 GHz, 800 MHz bus)
CPU MHz: 3400
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4x1024 MB DDR-RAM PC-2700R
Disk Subsystem: Fujitsu MAS3184NC (SCSI U320 15 krpm)
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
Compiler: Intel C/C++ Compiler 8.1 (20050405Z) for 32-bit applications
Intel Fortran Compiler 8.1 (20050405Z) for 32-bit applications
Microsoft Visual Studio .Net 2003 7.1.3088 (for libraries)
SmartHeap Library Version 6.03a from http://www.microquill.com
File System: NTFS
System State: default

Notes/Tuning Information

GENERAL

+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use

Portability flags

178.galgel: -FI /F32000000

Base tuning flags

-fast -Qansi_alias +FDO shlw32M.lib

Peak tuning flags

same as baseline (basepeak=yes set globally)

The system bus runs at 800 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY TX200 S2, 64-bit Intel Xeon 3.40 GHz

SPECfp2000 = 1668

SPECfp_base2000 = 1668

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: May-2005 | Hardware Avail: Mar-2005 | Software Avail: Mar-2005

Notes/Tuning Information (Continued)

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>