



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM eServer xSeries 236 (3.2 GHz Intel Xeon)

SPECint_rate2000 = 37.0
SPECint_rate_base2000 = 36.1

SPEC license #: 11 | Tested by: IBM, Research Trinagle Park, NC | Test date: Jun-2005 | Hardware Avail: Feb-2005 | Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	4	194	33.4	4	196	33.2
175.vpr	4	255	25.5	4	255	25.5
176.gcc	4	104	49.0	4	104	49.0
181.mcf	4	360	23.2	4	360	23.2
186.crafty	4	165	28.1	4	160	29.0
197.parser	4	230	36.3	4	230	36.3
252.eon	4	133	45.4	4	132	45.7
253.perlbnk	4	223	37.5	4	207	40.3
254.gap	4	123	41.5	4	123	41.5
255.vortex	4	151	58.2	4	151	58.3
256.bzip2	4	215	32.4	4	215	32.3
300.twolf	4	369	37.7	4	308	45.2

Hardware

CPU: Intel Xeon (3.2 GHz Xeon, 2MB L2 Cache, 800 MHz system bus)
 CPU MHz: 3200
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology enabled)
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
 Secondary Cache: 2048KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 512 MB ECC PC2-3200 Single Rank
 Disk Subsystem: 73GB SCSI 10K RPM
 Other Hardware:

Software

Operating System: Windows Server 2003 Standard Edition
 Compiler: Intel C/C++ Compiler 8.1 (20050409) for 32-bit applications
 Intel Fortran Compiler 8.1 (20050405Z) for 32-bit applications
 Microsoft Visual Studio .NET 13.0.9466 (for libraries)
 MicroQuill Smartheap Library 7.30
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
 +FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast -QxP -Qansi_alias +FDO
 C++: -QxP -Qipo -Qcxx_features +FDO

PEAK TUNING

164.zip: -fast -QxP -Qansi_alias -Oa +FDO
 175.vpr: basepeak=yes
 176.gcc: basepeak=yes
 181.mcf: basepeak=yes
 186.crafty: -fast -QxP -Oa +FDO shlW32M.lib
 197.parser: basepeak=yes
 252.eon: -fast -QxP +FDO
 253.perlbnk: -fast -QxP -Qansi_alias +FDO shlW32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation
IBM eServer xSeries 236 (3.2 GHz Intel Xeon)

SPECint_rate2000 = 37.0
SPECint_rate_base2000 = 36.1

SPEC license #: 11 | Tested by: IBM, Research Triangle Park, NC | Test date: Jun-2005 | Hardware Avail: Feb-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

```
254.gap:      basepeak=yes
255.vortex    -fast -QxP +FDO
256.bzip2:    -fast -QxP -Qunroll1 -Oa +FDO
300.twolf:    -fast -QxP +FDO shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib:  MicroQuill SmartHeap Library 7.3
              www.microquill.com
```