



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL385 (AMD Opteron (TM) 275)

SPECint_rate2000 = 66.9
SPECint_rate_base2000 = 60.6

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jul-2005 Hardware Avail: Jul-2005 Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	106	61.1	4	104	62.2
175.vpr	4	136	47.9	4	131	49.5
176.gcc	4	74.7	68.3	4	74.7	68.3
181.mcf	4	353	23.6	4	220	38.0
186.crafty	4	53.5	86.8	4	53.3	87.1
197.parser	4	177	47.2	4	145	57.5
252.eon	4	62.2	97.0	4	55.7	108
253.perlbnk	4	120	69.4	4	113	74.2
254.gap	4	82.4	61.9	4	82.3	62.0
255.vortex	4	87.2	101	4	85.1	104
256.bzip2	4	126	55.2	4	126	55.2
300.twolf	4	253	54.9	4	196	71.1

Hardware

CPU: AMD Opteron (TM) 275
 CPU MHz: 2200
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD (on chip) per core
 Secondary Cache: 1024KB(I+D) (on chip) per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x2048MB PC3200 DDR CL3.0
 Disk Subsystem: 1x36GB 15K Ultra320 SCSI
 Other Hardware:

Software

Operating System: SuSE Linux Enterprise Server 9 (x86_64) SP 1
 SuSE kernel 2.6.5-7.139-smp
 Compiler: PathScale EKO Compiler Suite, Release 2.1
 File System: Linux/ext2
 System State: Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
Base tuning for C programs: -O3 -ipa +FDO
Base tuning for C++ programs: -Ofast +FDO
Portability flags:
186.crafty: -DLINUX_i386
252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64 srcalt=fmax_errno
253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
           -DSPEC_CPU2000_GLIBC22 -DSPEC_CPU2000_LP64
254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
          -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
          -DSPEC_CPU2000_LP64
255.vortex: -DSPEC_CPU2000_LP64 srcalt=closed_files
Peak tuning:
164.gzip: -Ofast +FDO
175.vpr: -O2 -ipa -OPT:alias=disjoint -CG:p2align_freq=500000 -INLINE:aggressive=on
          -IPA:space=300:plimit=10000:callee_limit=5000:linear=on +FDO
176.gcc: basepeak=true
181.mcf: -O3 -ipa -IPA:field_reorder=on -m32 +FDO
186.crafty: -Ofast +FDO
197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL385 (AMD Opteron (TM) 275)

SPECint_rate2000 = 66.9
SPECint_rate_base2000 = 60.6

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jul-2005 | Hardware Avail: Jul-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

```

252.eon:      -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -OPT:treeheight=on
              -TENV:X=4:frame_pointer=off -fno-exceptions -LNO:fu=10:full_unroll_outer=on
              -IPA:plimit=4000:pu_reorder=1 +FDO
253.perlbnk: -O3 -ipa -IPA:plimit=10000 +FDO
254.gap:      -O3 -ipa -OPT:transform_to_memlib=on
255.vortex:   -Ofast -IPA:space=70:plimit=3000
              -OPT:goto=off:unroll_analysis=off:unroll_size=0:unroll_times_max=8
256.bzip2:    basepeak=true
300.twolf:    -O2 -OPT:unroll_times_max=8:unroll_size=256:alias=disjoint:Ofast
              -CG:gcm=off:p2align_freq=100000 -WOPT:mem_opnds=on -m32 +FDO

```

BIOS Configuration Notes
Node Interleaving Disabled

Other Configuration Notes
Taskset utility used to bind process to CPU(s)