



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM
IBM eServer e326 (AMD Opteron (TM) 252)

SPECfp_rate2000 = 46.6
SPECfp_rate_base2000 = 42.7

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Jun-2005 | Hardware Avail: Feb-2005 | Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	62.3	59.6	2	56.0	66.3
171.swim	2	126	56.9	2	126	57.1
172.mgrid	2	106	39.4	2	98.4	42.4
173.applu	2	104	47.0	2	94.9	51.3
177.mesa	2	69.5	46.8	2	65.0	49.9
178.galgel	2	95.8	70.2	2	87.3	77.1
179.art	2	107	56.5	2	73.4	82.2
183.quake	2	83.5	36.1	2	76.0	39.7
187.facerec	2	77.8	56.6	2	75.2	58.6
188.amp	2	161	31.8	2	150	34.1
189.lucas	2	110	42.1	2	110	42.1
191.fma3d	2	138	35.4	2	130	37.5
200.sixtrack	2	146	17.5	2	126	20.2
301.apsi	2	177	34.1	2	174	34.7

Hardware

CPU: AMD Opteron 252
CPU MHz: 2600
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 64KBI + 64KBD on chip
Secondary Cache: 1024KB (I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 1GB, DDR400
Disk Subsystem: SCSI, 36GB 10K RPM
Other Hardware: None

Software

Operating System: SuSE Linux 9.0 SP1 SLES 64 bit Kernel 2.6.5-7.139-smp
Compiler: PathScale EKOPATH(TM) Compiler Suite, Release 2.1
AMD Core Math Library 2.5.1
File System: Linux/reiserfs
System State: Multi-user, run level 3

Notes/Tuning Information

Tested by IBM Corporation
+ACML: Linked with AMD Core Math Library
Base tuning for C programs: -Ofast -WOPT:mem_opnds=on +FDO
Base tuning for FORTRAN programs: -Ofast -LNO:fusion=2 -OPT:fast_complex
Portability flags:
178.galgel: -fixedform
Peak tuning:
168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3
-OPT:unroll_times_max=8:unroll_size=128:IEEE NaN_Inf=off:ro=3 -TENV:X=4
-IPA:space=1000:linear=on:plimit=50000:callee_limit=5000
-INLINE:aggressive=on +FDO
171.swim: -Ofast -LNO:fusion=2
172.mgrid: -O3 -LNO:fusion=2:blocking=off
-OPT:Ofast:unroll_times_max=8:unroll_size=256:ro=3 -CG:gcm=off:cflow=off
173.applu: -Ofast -CG:local_fwd_sched=on
-LNO:fusion=2:fission=2:full_unroll_size=10000:prefetch=3
-OPT:ro=3 -TENV:X=3 -WOPT:val=2



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM

IBM eServer e326 (AMD Opteron (TM) 252)

SPECfp_rate2000 = 46.6

SPECfp_rate_base2000 = 42.7

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Jun-2005 | Hardware Avail: Feb-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

```

177.mesa:      -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +FDO
178.galgel:    -Ofast -OPT:fast_complex -CG:use_movlpd=on RM_SOURCES=lapak.f90 +ACML
179.art:       -O3 -OPT:ro=2:div_split=on:alias=typed -fno-math-errno -m32 +FDO
183.quake:     -Ofast -WOPT:mem_opnds=on -CG:local_fwd_sched=on -m32
187.facerec:   -Ofast -OPT:treeheight=on:IEEE_NaN_Inf=off:ro=3 -CG:load_exe=0
               -LNO:fusion=2 -IPA:plimit=1500 +FDO
188.ampp:      -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
               -fno-math-errno -TENV:X=4 -LNO:prefetch=0 +FDO
189.lucas:     -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 +FDO
191.fma3d:     -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
               -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack:  -Ofast -CG:load_exe=1 +FDO
301.apsi:      -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0

```

BIOS Configuration Notes
Node Interleaving is Disabled

Other Configuration Notes
Taskset utility used to bind process to CPU(s)