



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itautec-Philco
Servidor Itautec BX200 (3.0 GHz Intel Xeon)

SPECfp_rate2000 = 30.2
SPECfp_rate_base2000 = 29.5

SPEC license #: 2784 | Tested by: Itautec-Philco | Test date: Jul-2005 | Hardware Avail: May-2005 | Software Avail: May-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	77.9	47.7	2	77.9	47.7
171.swim	2	266	27.1	2	266	27.1
172.mgrid	2	177	23.6	2	177	23.6
173.applu	2	216	22.6	2	210	23.2
177.mesa	2	106	30.5	2	106	30.5
178.galgel	2	107	63.1	2	107	63.1
179.art	2	91.3	66.1	2	91.3	66.1
183.quake	2	108	27.9	2	81.4	37.1
187.facerec	2	133	33.0	2	133	33.0
188.amp	2	209	24.4	2	209	24.4
189.lucas	2	178	26.1	2	177	26.1
191.fma3d	2	204	23.9	2	204	23.9
200.sixtrack	2	203	12.6	2	201	12.7
301.apsi	2	243	24.8	2	249	24.2

Hardware

CPU: Intel Xeon (3.0 GHz Xeon, 2MB L2 Cache, 800 MHz system bus)
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology disabled)
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
 Secondary Cache: 2048KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4 x 1024 MB ECC DDR2 Single Rank
 Disk Subsystem: 73GB SCSI 10K RPM U320
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition
 Compiler: Intel C/C++ Compiler 8.1 for 32-bit Build 20050201Z
 Intel Fortran Compiler 8.1 for 32-bit Build 20050201Z
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)
 Microquill SmartHeap Library 7
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
 +FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

178.galgel: -FI /F32000000

BASE TUNING

C/F77/F90: -fast -QxP -Qansi_alias +FDO

PEAK TUNING

168.wupwise: basepeak=yes
 171.swim: -fast -QxP -f77rtl +FDO
 172.mgrid: basepeak=yes
 173.applu: -fast -QxP -Qscalar_rep- -Qauto -f77rtl +FDO
 177.mesa: basepeak=yes
 178.galgel: basepeak=yes
 179.art: basepeak=yes
 183.quake: -fast -QxP -Qansi_alias -Oa -Qrcd +FDO shlw32M2.lib
 187.facerec: basepeak=yes



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itautec-Philco

Servidor Itautec BX200 (3.0 GHz Intel Xeon)

SPECfp_rate2000 = 30.2

SPECfp_rate_base2000 = 29.5

SPEC license #: 2784 | Tested by: Itautec-Philco | Test date: Jul-2005 | Hardware Avail: May-2005 | Software Avail: May-2005

Notes/Tuning Information (Continued)

188. ammp: basepeak=yes
189. lucas: -fast -QxP
191. fma3d: basepeak=yes srcalt windowsdp
200. sixtrack: -QxP -Qipo +FDO
301. psi: -fast -QxP -f77rtl +FDO
EXTRA LIBRARIES
shlw32M2.lib: MicroQuill SmartHeap Library 7
www.microquill.com