



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro PDSMP-8/i Motherboard

SPECint2000 = 1489
SPECint_base2000 = 1490

SPEC license #01176 Tested by: Supermicro Test date: Aug-2005 Hardware Avail: Aug-2005 Software Avail: Apr-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
164.gzip	1400	131	1070	132	1059	[Bar chart showing ratio 1059]			
175.vpr	1400	146	958	144	971	[Bar chart showing ratio 971]			
176.gcc	1100	61.5	1788	61.5	1788	[Bar chart showing ratio 1788]			
181.mcf	1800	124	1451	124	1451	[Bar chart showing ratio 1451]			
186.crafty	1000	84.1	1189	84.6	1182	[Bar chart showing ratio 1182]			
197.parser	1800	141	1273	141	1273	[Bar chart showing ratio 1273]			
252.eon	1300	64.7	2011	64.8	2007	[Bar chart showing ratio 2007]			
253.perlbmk	1800	92.9	1937	93.4	1927	[Bar chart showing ratio 1927]			
254.gap	1100	62.3	1767	62.3	1767	[Bar chart showing ratio 1767]			
255.vortex	1900	74.6	2548	74.6	2548	[Bar chart showing ratio 2548]			
256.bzip2	1500	139	1080	139	1080	[Bar chart showing ratio 1080]			
300.twolf	3000	190	1576	191	1573	[Bar chart showing ratio 1573]			

Hardware

CPU: Intel Pentium D 840 Processor (3.2GHz, 800 MHz bus)
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD/core on chip
Secondary Cache: 1024KB/core on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4 X 1024MB DDR2-667 ECC Unbuffered
Disk Subsystem: 1 X IDE Maxtor DiamondMax Plus 9 250GB
Other Hardware: N/A

Software

Operating System: Windows 2003 Enterprise Server
Compiler: Intel C++ Compiler 9.0 Build 20050430Z (32-bit)
Microsoft Visual Studio .Net 2003(for libraries)
SmartHeap Library Version 7.4 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlW32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: Approved stdcpp src.alt used
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbmk: -fast -Qansi_alias +FDO shlW32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro
PDSMP-8/i Motherboard

SPECint2000 =	1489
SPECint_base2000 =	1490

SPEC license #01176 | Tested by: Supermicro | Test date: Aug-2005 | Hardware Avail: Aug-2005 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll11 +FDO

300.twolf: -fast -O3 +FDO shlw32M.lib

New 32-bit Windows tools used, approved in May-2005

Tested system was built with 1U SC816S-400 -Redundant Power Supply. Use only with Supermicro 1U chassis recommended

Product description located as of:

<http://www.supermicro.com/products/motherboard/DualCore/E7230/PDSMP-8.cfm>

The system bus runs at 800MHz